

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor Secs 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 Survey by - S.C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCS0 records Vol. 13 Page(s) 5537)

Set dogwood post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 1, 2, 11, & 12, marked T28S S 1 on NE, R3W S 12 on SE, S 11 on SW, S 2 on NW faces, with 1 notch on E & 5 on S edges; from which
An Ash, 14" dia. bears N.22°E. 48 lks. mkd: T28S R3W S1 BT
A fir, 14" dia. bears S.30°E. 39 lks. mkd: T28S R3W S12 BT
A fir, 14" dia. bears S.20°W., 9 lks. mkd: T28S R3W S11 BT
A fir, 10" dia. bears N.45°W., 90 lks. mkd: T28S R3W S2 BT

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm. Stoffel - Aug. 1962 - C.S. File 52/126-40

Found - Orig. 14" now 27" fir S.30°E., 25.7 ft. shows good bark scribing.
No other orig. BTs fd.
Find 3/4" IR at corner.
Note - Call to Cavitt Creek to East, checks OK
New BTs- Rescribe now 27" R.Fir S.30°E., 28.4 ft. S12 T28S R3W CS BT.
24" W.Fir bears N.13½°E., 11.2 ft. scribed S1 T28S R3W CS BT.
10" W.Fir bears S.21°W., 26.0 ft. scribed S11 T28S R3W CS BT.
8" Yewood bears N.5°W., 28.8 ft. scribed S2 CS BT.

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Jan. 1965 - C.S. File 51/254-25

Found - 2½" alum. cap.
27" D.Fir S.30°E., 28.4 ft. scribed S12 T28S R3W CS BT. Cut high stump above scribe.
24" W.Fir N.13½°E., 11.2 ft. scribed S1 T28S R3W CS BT. Cut high stump above scribe.
10" W.Fir S.21°W., 26 ft. scribed S11 T28S R3W CS BT
8" Yewood N.5°W., 28.8 ft. scribed S2 CS BT.
New BTs- 6" W.Fir N.75½°E., 10.3 ft. scribed S1 BT, Alum tag RE4287
8" Yew S.57°E., 19.8 ft. scribed S12 BT, Alum tag RE4287

continued next page

1

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor Secs 1, 2, 11, & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas County Surveyors Office - Randall Smith & Stephen
Flause - Jan. 21, 1997 - C.S. 64/71-10

Found - 2½" dia. alum cap on a 1" OD iron pipe protrudes 10"
above ground, markings on top of cap orientated
west (set by Thomas Shrum date unknown)

US PROPERTY COR.
T28S R3W
S 2 | S 1
S11 | S12
RE 4278

- 3/4" I.R. noted in 1962 ren. by DCSO not seen.
- 14" now 27" Dia. 4' high D.Fir stump, with an
unhealed double blaze, scribing visible "T28S R3W
S12 BT", bears S.33°E., 28.4'. OBT
- 10" now 10" dia. 2' high rotted D.Fir stump, with
scribing visible "T28S R3W S11 CS BT", bears
S.19°W., 26'.
- 8" now 10" dia. Yew, with an unhealed double blaze,
scribing visible "S2 CS BT", bears N.5°W., 28.8'.
- 6" now 14" dia. W.Fir, with a fully healed double
blaze, scribing bears N.72½°E., 10.3'.
- 24" now rotted W.Fir Stump no blazes or scribing
visible, bears N.13½°E., 11.2'.
- 8" now 10" dia. Yew, with an unhealed double blaze,
scribing visible "S12 BT", and alum. tag in
lower blaze "RE 4287", bears S.57°E., 19.8'.
- New - 14" dia. D.Fir double blazed and scribed "T28S R3W
S2 CS BT", bears N.62°W., 17.3'.