

PRIMARY CORNER DESCRIPTION CC Secs. 23 & 24 (North)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by - S.C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO records Vol. 13 Page(s) 5533-4)

Set cedar post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 13, 14, 23, & 24, marked T28S S 13 on NE, R3W S 24 on SE, S 23 on SW, S 14 on NW faces, with 1 notch on E & 3 on S edges; from which
A fir, 36" dia. bears N.34°E. 49 lks. mkd: T28S R3W S13 BT
A fir, 36" dia. bears S.55°E. 63 lks. mkd: T28S R3W S24 BT
A fir, 40" dia. bears S.35°E. 55 lks. mkd: T28S R3W S23 BT
A fir, 30" dia. bears N.64°W. 65 lks. mkd: T28S R3W S14 BT

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5555)

Point of intersection bet. secs. 23 & 24.
Set stone, 6x6x16" 11" in the ground for closing cor. secs. 23 & 24, marked CC on S face with 1 groove on E & 5 grooves on W face, from which:
A fir, 14" dia. bears S.27°E. 13 lks. mkd: T28S R3W S24 BT
A fir, 18" dia. bears S.52°W. 62 lks. mkd: T28S R3W S23 BT

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Dec. 1960 - M11-79

Found - Stone 6"x6"x11"
18" fir, S.27°E., 8.6 ft. (down)
22" fir, S.52°W., 42.5 ft. (stump)
Set - 3/4"x36" iron rod (W/alum cap 5/25/1978 per D. Gaylord)
5" Yew S.1°30'W., 33.6 ft.
15" Fir, N.85°E., 64.5 ft.
15" Fir, S.24°30'E., 58.8 ft.

Maurice E. Farr - March 17, 1988 - C.S. 63/73-2

Found - 1" iron rod, firmly set, projecting 30" above a 2 ft. mound of stone with a 2 1/4" alum, cap mkd "USPC Property Corner Do not Disturb 13 RE 4287"
23 24
Orig. BT, a 24 D.Fir stump, S.52°W., 42.2 ft. (Rec. 40.92 ft.) with a healed blaze.
16" D.Fir, N.85°E., 64.5 ft. with scribe marks "S13 RE4287 CC" visible on a partially healed double blaze.

continued next page

PRIMARY CORNER DESCRIPTION CC Secs. 23 & 24 (North)

Alias	Description

A roothole, S.24½°E., 58.8 ft. with a downed 15" D.Fir alongside with a partially healed double blaze.

A 6" Yewwood, S.1½°W., 33.1 ft. (Rec. 33.6 ft.) with scribe marks "S23 RE4287 CC" visible on a partially healed double blaze.

Set - I add a 3 ft. mound of stone to the found monument which now projects 20". From which -

At the true closing corner point per M70-36, I set a 6 ft. steel fence post, driven 2 ft. in the ground as a guard post, S.0½°E., 2.1 ft. with Forest Service signs #54-2 & 54-4 attached.

New BT - 5" hemlock S.30°E., 26.5 ft. scribed "T28S R3W S24 CC BT" on a single blaze with a 3/4" dia., brass washer, stamped "LS1181" nailed flush to the base of the blaze.

To reach 2.2 mi. past the end of pavement on Cavitt Creek Rd. No. 25, turn west onto rd. #28-3-15 (Champion Rd. #CC900) Drive 1.9 mi. and turn left onto Rd. #28-3-11 (CC920). Drive 2.8 mi & turn left onto Forest Rd. No. 1800-127. Drive 0.2 mi to the sec. line crossing. The corner is approx. 150 ft. west of the road at the culvert.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2274, Surveyed Oct/Nov 2009 - (DCSO records Vol. 56 Page(s) 22297)

The closing cor. of secs. 23 & 24, perpetuated by Shrum, Jr., in 1960, subsequently perpetuated by Gaylord, in 1978, and further perpetuated by Farr, in 1988, monumented with an iron post, 1" dia., firmly set, projecting 18" above the top of a mound of stone, 2 ft. diam., 1 ft. high, (with the orig. basalt stone, 6x12x14", no marks visible, incorporated into the stone mound), with brass cap (properly) mkd. from which the remains of an orig. bearing tree

A sawed fir stump, 26" dia., bears S.52°W., 40.9 ft., with a healed blaze.

and the remains of bearing trees mkd. by Shrum, Jr.

A fir, 19" dia., bears N.84¼°E., 64.5 ft., with fragmentary scribe marks visible on a partially healed blaze.

A roothole bears S.28°E., 60.4 ft., alongside of which is a down fir snag, 15" dia., with no marks visible.

A yew, 8" dia., bears S.2¼°W., 33.2 ft., with fragmentary scribe marks visible on a partially healed blaze.

and a bearing tree mkd. by Farr

A hemlock, 15" dia., bears S.38¾°E., 26.5 ft., with a healed blaze.

continued next page

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 602400

PRIMARY CORNER DESCRIPTION CC Secs. 23 & 24 (North)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Corner is located 185 ft. S. of a gravel road, 12 ft. wide,
on a broken NE. slope.
CC Secs. 13 & 14 (South) bears S.88°20'03"W., 74.00'