

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 639700

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 36 only, T27-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by S.C. Flint, Contract #454, dated June 19, 1882
(DCSO records Vol. 12 Page(s) 4978)

Set Laurel post 3 ft. long, 3" sq., for ¼ sec.cor. mkd. S C
¼ S on N. face, from which

A Fir 20" dia., bears S.53°E., 79 lks. dist. mkd. SC ¼ S
BT.

A Fir 30" dia., bears N.40°E., 56 lks. dist. mkd. SC ¼ S
BT.

Douglas Co. Surveyors Office - James Byron, Deputy - John
Powell & Wm. Stoffel, crew - Aug. 1962 - C.S. File 52/126-42

Found - Orig. NE. BT, now down.
Orig. 20" now 38" R.Fir, S.53°E., 52.1 ft., shows
good bark scribing.

Set Brass cap at cor. mkd: County Surveyors Office
T 27 S R 3 W
South ¼ S36
1962

New BTs- Rescribe O.B.T., 38" R.Fir S.53°E., 54.9 ft. "¼ S CS
BT"

5" R.Fir bears N.66°W., 24.4 ft. scribed "¼ S36 CS
BT"

Corner is at base of Laurel stool.