

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5554)

Set stone 8x12x16", 11" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
 A fir, 40" dia., bears N.40°W., 53 lks., mkd: ¼ S24 BT.
 A fir, 24" dia., bears S.54°W., 206 lks., mkd: ¼ S25 BT.
House, Scott Morrison, bears S.50°E., 2 chs.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm. Stoffel - Sept. 1962 - C.S. File 52/126-55

Found - Orig. 40", now 48" Fir Snag N.30°W., not N.40°W. 35.0 ft., shows good scribing.
 Orig. 24", now dead 36" Fir, S.44°W., not S. 54°W., 136.0 ft., shows scribing.
 Find Stone at Cor as recorded except chiseled not fd
Set - Brass Cap alongside Cor. Stone & Mkd: County Surveyors Office, 1962 ¼ S24/S25 T28S R3W
New BTs- 11" R.Fir bears N.46°E. 25.0 ft. scribed ¼ S24 CS BT
 12" R.Fir bears S.9°E. 5.6 ft. scribed ¼ S24 CS BT.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2274, Surveyed Oct/Nov 2009 - (DCSO records Vol. 56 Page(s) 22299)

The ¼ sec. cor. of secs. 24 & 25, perpetuated by Byron, in 1962, monumented with an iron post, 1¼" dia., firmly set, projecting 12" above ground, (alongside of which is the orig. basalt stone, 8x12x16", lying loose on the ground, with marks ¼ visible on a face) with brass cap (properly) mkd. from which the remains of the orig. bearing trees
 A decayed fir stump, size indeterminate, bears S.41°W., 136.0 ft., with no marks visible. (Record S.54°W.)
 A fir snag, 46" dia., bears N.28¾°W., 35.0 ft., with scribe marks ¼ S24 visible on a partially healed blaze. (Record N.40°W.)
and bearing trees mkd. by Byron
 A fir, 23" dia., bears N.46°E., 25.5 ft., with a healed blaze.
 A fir, 26" dia., bears S.15¾°E., 5.5 ft., with a healed double blaze.
Bury the orig. stone alongside the iron post.
Corner is located on a broken N. slope.