TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 13 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - S.C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO records Vol. 13 Page(s) 5534)

Set post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked on N & S faces ¼ S; from which
A fir, 36" dia., bears N.21°W., 39 lks., mkd: ¼ S BT.
A yew, 12" dia., bears S.35°W., 41 lks., mkd: ¼ S BT.

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5555)

1/4 sec. cor., which is a stake marked & witnessed as described by the Surveyor General.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Mike Stone - Sept 1962 - C.S. File 52/126-51

Found - Orig. 12" now 14" yewood snag S.55°W., not S.35°W., 27.1 ft. shows good scribing.
Orig. 36" now 40" low cut fir stump, N.21°W., 25.7 ft., no scribing found.
Set - Brass cap at cor. mkd: County Surveyors Office 1962 South ¼ S13 T28S R3W
New BTs- 34" hemlock bears N.85°W., 11.0 ft. scribed S¼ S13 CS BT.
8" Yewood bears N.71°E., 5.7 ft scribed S¼ S13 CS BT

Gerald V. Nygren - For: USFS - March 1988 - C.S. 63/69-12

Found - 1" galv. iron pipe with 2½" brass cap flush with ground marked "COUNTY SURVEYORS OFFICE T28S ¼ S13 R3W 1962
Brass cap, ¼ for sec. 24 bears N.89°34'E., 12.24 ft.
8" Yew, bears N.58°E., 6.1 ft. (vis. scribe)
14" Yew snag, bears S.55½°W., 27.1 ft. (vis. scribe)
34" Hemlock stump, bears N.84½°W., 11.0 ft. (vis. scribe)
New BT - 13" Hemlock, bears N.63°W., 35.8 ft. scribed "T28S R3W ¼ S13 BT" with brass washer stamped "RLS 1035" nailed flush to the lower end of the blaze.