

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION 1/4 cor. for Sec. 36; & 31, T28-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5427)

Set granite stone 8x10x15 ins., 10" in the ground for 1/4 sec. cor. mkd. 1/4 on W. face, from which
A Fir 10" dia., bears S.79°E., 27 lks. dist. mkd. 1/4 S31 BT.
A Fir 7" dia., bears S.66°W., 6 lks. dist. mkd. 1/4 S36 BT

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell & Wm. Stoffel, crew - Aug/Sept. 1962 - C.S. File 52/126-1

Found stone at corner and BTs, all as recorded. SW BT has previously been opened, shows good scribing.
Set Brass cap at cor. mkd: County Surveyors Office
(BC set alongside cor. stone) T 28 S
1/4
R3W S 36 | S 31 R2W
1962
New BT - 13" R.Fir bears S.41°W., 10.0 ft. scribed 1/4 S36 CS BT.

Brent Knapp, i.e. engineering - Crew: N. Fromdahl, J. Ogden, and L. Heddens - 9/2022 - C.S. File 65/111-13

Found - Brass Cap with stone (properly mkd)
14" Fir, S79°E, 17.8', down
New - 9" Cedar, N.25°(E). 9.1', scribed "1/4 S31 BT"
16" Cedar, S.24°E., 30.3', scribed "1/4 S31 BT"
39" D.Fir, N.51°W., 10.2', scribed "1/4 S36 BT"
5" Cedar, N.25°W., 11.2', scribed "X"
Note - Compass decl. 15°E.