

PRIMARY CORNER DESCRIPTION Sec Cor for 25 & 36; 30 & 31, T28-2

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5427)

 Set Fir post 3 ft. long, 4" sq., 24" in the ground for cor. secs. 30, 31, 25 and 36, marked T28S S30 on NE.; R2W S31 on SE.; R3W S36 on SW.; and S25 on NW. face, with 5 notches on N. and 1 notch on S. edge, from which
 A Fir 5" dia., bears N.13°30'E., 31 lks. dist. mkd. T28S R2W S31 BT.
 A Chinquapin 5" dia., bears S.43°15'E., 31 lks. dist. mkd. T28S R2W S31 BT.
 A Fir 6" dia., bears S.15°W., 53 lks. dist. mkd. T28S R3W S36 BT.
 A Fir 8" dia., bears N.60°W., 42 lks. dist. mkd. T28S R3W S25 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell & Wm. Stoffel, crew - Aug/Sept. 1962 - C.S. File 52/126-3

 Found all original BTs, SE. BT dead. All check record except dist. to NW. BT, should be 41.0 ft., not 27.7 ft. NW. and SE. BTs show scribing.
 Set Brass cap at cor. mkd: County Surveyors Office

	T 28 S		
R3W	S 25 S 30	R2W	
	S 36 S 31		
	1962		

 New BT - 7" R.Fir bears S.58°E., 10.9 ft. scribed S31 CSBT.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2500, Surveyed Aug. 2011 - (DCSO records BLM Plat T28-2W 2012-1 & Vol. 58 Page(s) 22942)

 The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., perpetuated by Byron, in 1962, monumented with an iron post, 1¼" dia.. firmly set, projecting 13" above ground, with brass cap (properly) mkd.
 from which the remaining original BTs
 A fir, 30" dia., bears N.13½°E., 20.5 ft., with a healed blaze.
 A fir, 14" dia., bears S.15°W., 33.7 ft., with a healed blaze. (Record 35.0 ft.)
 A fir, 33" dia., bears N.60°W., 40.9 ft., with a healed blaze. (Record, 27.7 ft.)
 and the remains of a bearing tree mkd. by Byron
 continued next page

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T28-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A decayed fir stump, 7" dia., bears S.60½°E., 11.2 ft.
with no marks visible.

and a new bearing tree

A fir, 10" dia., bears S.33°E., 39.9 ft., mkd. T28S R2W
S31 BT.

Corner is located 155 ft. W. of a shallow draw, drains
generally NW.

Latitude 43°05'54.19"N. Longitude 122°59'30.79"W.
(NAD 1983 (CORS 96))