



PRIMARY CORNER DESCRIPTION Sec Cor for 24 & 25; 19 & 30, T28-2

Alias	Description
Alias	Description
Alias	Description
Alias	Description

18" Chinquapin Oak bears S.14½°W., 102.5 ft. visible scribe.  
40" Hemlock stump bears S.14°E., 23.4 ft., visible scribe.  
36" D.Fir stump bears S.29°W., 19.7 ft., blaze healed.  
36" D.Fir stump bears N.50°W., 15.8 ft., visible scribe.  
New BTs- 8" Chinquapin Oak S.52°E, 45.0 ft. scribed "S30 T28S R2W BT"  
5" Hemlock bears N.85°E., 43.3 ft. scribed X BT.  
Brass washers stamped "RLS 1035" were nailed flush with the lower portion of the blazes.  
No tree available in the NW. quadrant.

Fd. as per C.S. 63/69 - by D.Edwards, 4/2011 - C.S. 65/74-6

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2274, Surveyed Oct/Nov 2009 - (DCSO records Vol. 56 Page(s) 22298)

-----

The cor. of secs. 19, 24, 25, & 30, on the E. bdy. of the Tp., perpetuated by Byron, in 1962, subsequently perpetuated by McLind, in 1978, and further perpetuated by Nygren, in 1988, monumented with an iron post, 1¼" dia., firmly set, projecting 16 ins. above ground, (alongside of which is the orig. igneous stone, 6x12x16", lying loose on the ground, with 4 notches visible on an edge and 2 notches visible on an adjacent edge) with brass cap (properly) mkd. from which the remains of the orig. bearing trees

A sawed fir stump, 33" dia., bears S.25°W., 19.1 ft., with a healed blaze. (Record 31.0 ft.)

A decayed hemlock stump, 30" dia., bears N.48°W., 15.8 ft., with scribe marks 28S / R3W 24 visible on an opened blaze.

and the remains of a bearing tree mkd. by Byron

A sawed hemlock stump, 35" dia., bears S.15½°E., 22.8 ft., with scribe marks 28S R2 S30 CS visible on a partially healed blaze.

and a bearing tree mkd. by McLind

A chinquapin, 19" dia., bears S.12½°W., 102.5 ft., with scribe marks T28S R visible on a partially healed blaze

and bearing trees mkd. by Nygren

A hemlock, 13" dia., bears N.81¼°E., 42.9 ft., with a healed double blaze.

A chinquapin, 12" dia., bears S.55¾°E., 45.0 ft., with scribe marks R2W visible on a partially healed blaze.

continued next page

2

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec Cor for 24 & 25; 19 & 30, T28-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and a new bearing tree

A fir, 4" dia., bears N.11°W., 27.7 ft., mkd. X BT.  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)  
driven at the base right side-center.

Bury the orig. stone alongside the iron post.  
Corner is located on a gradual NE. slope.

The geographic position (NAD 1983 (CORS)) of the following  
corners, as determined by ties from temporary GPS control  
points, established utilizing dual frequency, carrier phase  
GPS receivers, using for control National Spatial Reference  
System Continuously Operating Reference Station (CORS) DODSON  
BUTTE CORS ARP, and National Cooperative CORS Network Station  
ROSEBURG COOP CORS ARP, is as follows:

Latitude: 43°06'46.23"N.      Longitude: 122°59'31.10"W.