

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec Cor for 13 & 24 only, (East)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by S.C. Flint, Contract #454, dated June 19, 1882  
- (DCSO records Vol. 13 Page(s) 5425-26)

-----  
Set Cedar post 4 ft. long, 4" sq., 24" in the ground for cor.  
to secs. 18, 19, 13 and 24, marked T28S S18 on NE.; R2W S19  
on SE.; R3W S24 on SW.; and S13 on NW. faces, with 3 notches  
on N. and S. edges, from which  
A Hemlock 20" dia., bears N.55°E., 56 lks. dist. mkd. T28S  
R2W S18 BT.  
A Hemlock 14" dia., bears S.20°E., 5 lks. dist. mkd. T28S  
R2W S19 BT.  
A Hemlock 24" dia., bears S.25°W., 15 lks. dist. mkd. T28S  
R3W S24 BT.  
A Cedar 20" dia., bears N.30°W., 8 lks. dist. mkd. T28S  
R3W S13 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - John  
Powell & Wm. Stoffel, crew - Sept. 1962 - C.S. File 52/126-52

-----  
Found all BTs as recorded. NW. BT shows good scribing.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 28 S  
R3W  $\frac{S\ 13}{S\ 24}$  | R2W  
1962  
Rescribe orig. 24" now 28" Hemlock S.25°W., 9.9 ft. 'S24 T28S  
R2W CS BT".

Fd. OK, March 1980 by BHW Engineering - M 83-19