

TOWNSHIP 28 RANGE 03 POINT IDENTIFIER # 700404

PRIMARY CORNER DESCRIPTION C C for Secs. 18 & 19, T28-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5471)

(Intersect N & S line, 4.92 chs. N. of cor. secs. 18, 19, 13 and 24) At intersection point
Set granite stone 5x10x16 ins., 11" in the ground for closing cor. secs. 18 and 19, marked CC on E. face, with 3 grooves on N. and S. faces, from which
 A Fir 20" dia., bears N.25°E., 35 lks. dist. mkd. T28S R2W S18 BT.
 A Laurel 6" dia., bears S.35°E., 11 lks. dist. mkd. T28S R2W S19 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell & Wm. Stoffel, crew - Sept. 1962 - C.S. File 52/126-52

Found stone at cor. and both BTs as recorded. NW. BT shows good scribing.
Do not set brass cap at corner.
New BT - 9" R.Fir bears S.43°E., 5.0 ft scribed "S19 CC T28S R2W CS BT".

Survey by Ronald A. Quimby, LS #1654, BHW Engineering - For: U.S. Forest Service - March 1980 - M 83-19

Found - Stone 1.94 ft. West of line. Set brass cap at location of stone, buried stone alongside.
 13" Hemlock bears S.43°E., 5.0 ft. from stone, good face.
 20" D.Fir bears N.25°E., 23.0 ft. from stone, visible scribes.
Set 2½" I.P. with brass cap mkd. "RLS 1654 T28S R3W S13 S18C S19C T28S R2W 1980." Set fiberglass post & signs 6.0 ft. South.
New BT - 7" Hemlock N.35°W., 16.4 ft. "S19 CC T28S R2W BT", brass washer RLS 1654 in BT face.