

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 1 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by S.C. Flint, Contract #454, dated June 19, 1882 (DCSO records Vol. 13 Page(s) 5423)</p> <p>-----</p> <p>Set Laurel post 3 ft. long, 3" sq., 24" in the ground for ¼ sec.cor. marked on E. and W. faces, ¼ S., from which A Fir 12" dia., bears N.80°W., 21 lks. dist. mkd. ¼ S BT A Fir 36" dia., bears N.65°E., 51 lks. dit. mkd. ¼ S BT.</p>
<p>Douglas Co. Surveyors Office - James Byron, Deputy - John Powell &amp; Wm. Stoffel, crew - Aug. 1962 - C.S. File 52/126-44</p> <p>-----</p> <p>Found - Orig. 12" now 18" Fir, N.80°W., 13.9 ft., shows faint bark scribing. Orig. 36" Fir now down, N.65°E., 33.7 ft., shows bark scribing.</p> <p>Set Brass cap at cor. mkd: County Surveyors Office East ¼ S 1   T28S R3W   R2W 1962</p> <p>New BTs- 15" Fir bears S.61°W., 31.9 ft. scribed E¼ S1 CS BT. 13" Cedar bears N.59½°W., 19.3 ft. scribed E¼ S1 CS BT.</p>
<p>Survey by Ronald A. Quimby - For: U.S. Forest Service - March 1980 - M 79-37</p> <p>-----</p> <p>Found - 1962 DCSO brass cap on 1¼" Iron pipe. 12" Cedar stump S.60°E., 120.2 ft.</p> <p>Fiberglass post and signs 4.0 ft. North and South.</p> <p>New BTs- 10" Pine S.10°E., 25.8 ft. "¼ S1 BT" 9" Cedar S.76°E., 15.5 ft. "¼ S1 BT"</p> <p>No trees in section 1. Brass washers in BT faces "RLS 1005"</p>
<p>Kristian DeGroot - June 1998 - C.S. File 65/20-35</p> <p>-----</p> <p>Found - 1¼" (O.D.) iron pipe, firmly set, projecting 18" above a 30" diameter mound of stone with a 2 1/2" brass cap properly stamped from which 12" Cedar rotted cedar stob bears N.60°W., 17.7 ft. (Rec. N.591/2°W., 19.3 ft.) 20" Pine bears S.10°E., 25.8 ft. with a healed double blaze. 14" Cedar bears S.76°E., 15.6 ft. with a healed double blaze.</p> <p>I paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all bearing trees</p>