

TOWNSHIP 28 RANGE 04E POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Cor. Secs 30, 31; 25, & 36 T28-3E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed Aug 1928/Aug 1929 - (DCSO records Vol. 25 Page(s) 10485)

Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for cor. of secs. 25, 30, 31, & 36, with brass cap mkd

T28S
R3E|R4E
S 25 | S 30
S 36 | S 31
1928

from which

- A fir, 28" dia., bears N.68°E., 17 lks., mkd: T28S R4E S30 BT.
- A fir, 26" dia., bears S.30°E., 56 lks., mkd: T28S R4E S31 BT.
- A fir, 24" dia., bears S.16°W., 30 lks., mkd: T28S R3E S36 BT.
- A fir, 48" dia., bears N.84½°W., 130 lks., mkd: T28S R3E S25 BT.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 9/8/2021 (filed 3/21/2023) - C.S. File 67/55-50

Found - 2½" dia., GL0 brass cap marked as described on a 1½" I.D. iron pipe projecting 9" above ground. Approx. 36" dia., 4 ft. tall rotted and broken fir stump. All noted scribing still legible on unhealed face. Stump bears S.30°E., 35.4 ft. No clear evidence of other BTs found.

New - 18" dia., W.Fir, not blazed or scribed Forest Service location tag marked S.70°W., 23.8 ft. We right side center spike tree and measure a bearing & distance of N.66°E., 24.0 ft. to tree. 35" dia., G.Fir as above but with tag marked N.72°W., 15.4 ft. We side spike and measure S.76°E., 15.9 ft. to tree.

Note - Corner on easterly edge of Alder thicket, on moderate NNW slope, approximately 85 ft. North of gravel forest access rd. Compass decl. 14½°E.