

TOWNSHIP 28 RANGE 04E POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Cor Secs 19, 30; 24, & 25 T28-3E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,  
under special instructions dated Dec. 27, 1920, Surveyed Aug  
1928/Aug 1929 - (DCSO records Vol. 25 Page(s) 10486-7)

-----  
Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for  
cor. of secs. 19, 24, 25, & 30, with brass cap mkd

T28S  
R3E|R4E  
S 24|S 19  
S 25|S 30  
1928

from which

- A fir, 40" dia., bears N.45°E., 26 lks., mkd: T28S R4E S19  
BT.
- A fir, 48" dia., bears S.1°E., 38 lks., mkd: T28S R4E S30  
BT.
- A fir, 24" dia., bears S.19°W., 91 lks., mkd: T28S R3E S25  
BT.
- A fir, 24" dia., bears N.35°W., 40 lks., mkd: T38S R3E S24  
BT.