

TOWNSHIP 28 RANGE 04E POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Cor. Secs. 6, 7; 1 & 12 T28-3E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed Aug 1928/Aug 1929 - (DCSO records Vol. 25 Page(s) 10490)

-----  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 1, 6, 7, & 12, with brass cap mkd

T28S	
R3E	R4E
S 1	S 6
S 12	S 7
1928	

from which

- A fir, 12" dia., bears N.42°E., 76 lks., mkd: T28S R4E S6 BT.
- A pine, 8" dia., bears S.80°E., 64 lks., mkd: T28S R4E S7 BT.
- A pine, 8" dia., bears S.50°W., 21 lks., mkd: T28S R3E S12 BT.
- A fir, 10" dia., bears N.18½°W., 61 lks., mkd: T28S R3E S1 BT.