

TOWNSHIP 28 RANGE 04E POINT IDENTIFIER # 107700

PRIMARY CORNER DESCRIPTION Cor. Township 27S Ranges 3 & 4 E. only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under special instructions dated Dec. 27, 1920, Surveyed Aug 1928/Aug 1929 - (DCSO records Vol. 25 Page(s) 10484)

East on the S bdy of sec. 36 at 65.65 chs: Old standard cor. of Ts. 27 S, Rs 3 & 4 E., bears N 4.29 chs. Now obliterated. (See Flint 1883 survey Vol. 24 Pg. 10051) AT 80 chs: Set an iron post, 3 ft. long, 3" dia., 27" in ground, for standard cor. of Ts. 27 S., Rs. 3 & 4 E., with brass cap mkd.

S C
T27S
R3E|R4E
S 36|S 31
T28S R4E
S 6
1929

from which

- A fir, 34" dia., bears N.59°E., 23 lks., mkd: S C T27S R4E S31 BT.
- A fir, 34" dia., bears N.31°W., 63 lks., mkd: S C T27S R3E S36 BT