

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 037010

PRIMARY CORNER DESCRIPTION SW Cor. Ledgerwood DLC #37

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Original survey by J.A. Burnett under Contract dated Jan. 8 1857

Set Post from which
A Laurel 12" dia., bears N.35°E., 18 lks.
Raised mound with trench as per instructions.

BLM resurvey by Lynn M. Roseberry, under Group #636. Survey, May/June 1967 (DCSO records, Vol. 34 Page 14201)

The point for the SW cor. DLC #37, restored by the method of broken boundaries; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

S 5 | C 37
T 28 S R 4 W
1967

from which

A Madrone 18" dia., bears N.46°E., 112 lks. dist., mkd.
C 37 BT.

A Fir 20" dia., bears N.55½°E., 78½ lks. dist., mkd.
C 37 BT.

Mark Smalley - For: Roseburg Resources - 5/9/2006 - C.S. 65/60-6

Found - 1967 BLM IPBC
25" Fir N.55½°E., 51.8 stump
Broken Madrone N.46°E., 73.9 now a bush
New BTs- 14" Fir N.52°W., 20.9 scribed "DLC BT"
29" Fir S.22°W., 9.4 scribed "DLC BT"