

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Cor. to Secs. 30 & 31; 25 & 36 T28-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - James E. Freeman, under contract # 1, dated  
May 28, 1851. (DCSO records Vol. 13 Pg. 5603)

-----  
Set post for corner from which:

- A Fir, 5" dia. bears N.20°E., 2 lks. dist.
- A Fir, 9" dia. bears S.60°E., 16 lks. dist.
- A Fir, 9" dia. bears S.70°W., 20 lks. dist.
- A Laurel, 8" dia. bears N.20°W., 40 lks. dist.

-----  
W.H. Byars, contract # 376, dated Jan. 22, 1881.  
(DCSO records Vol. 13, Pg. 5611)

-----  
Set new post as per instructions, bearing trees all standing  
and visible. (Same as 1851 bearing trees)

-----  
Doug. County Surveyor's Office - James W. Byron, Dale  
McFarland, Jim Powell, Aug. & Sept. 1961. C.S. File 49/67-29

-----  
Found - Orig. 9" now 30" Fir stump S.70°W., 13.2'. We open  
& find good scribing "S3".

Stump section that checks record S.E. BT.

Orig. N.W. & N.E. Bt's not found.

Set - Brass Cap at corner mkd:

County Surveyor's Office

S25 | S30 T28S

R5W S36 | S31 R4W

1961

New BTs - 21" R.Fir, bears N.37°W., 12.0' mkd: S25 T28S R5W  
CS BT.

24" R.Fir, bears N.17½°E., 49.7' mkd: S30 T28S R4W  
CS BT.

18" Laurel, bears S.17°W., 43.4' mkd: S36 T28S R5W  
CS BT.

No trees near to S.E.

-----  
Fd. OK, Wm. Ruppert, Jan/March 1983, M 93-68

Fd. OK, by Ruppert, May 1996 - Partition Plat 1996-0082