

PRIMARY CORNER DESCRIPTION ¼ Cor. Sec. 30; & Sec. 25 T28-5.

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - James E. Freeman, under contract #1 dated May 28, 1851. (DCSO rec. Vol. 13, Pg. 5603)

Set post for ¼ Corner from which:
A Laurel, 6" dia. bears N.5°E., 115 lks. dist.
A Laurel, 4" dia. bears S.75°W., 15 lks. dist.

B.A. Shaner, for: Paul B. Hult Lbr. Co. July 1964. M 22-57 & C.S. File no. 51/296.

Found - 24" Madrone, original BT with axe marks on face but scribes now rotted out, said face overgrown by wood 80+ years old, bears S.75°W., 9.9'.
18" Madrone, probable original BT, bears N.5°E., 87.3'. (rec. 75.9')
Set - 5/8" Iron Rod.
New BTs - 18" D.Fir, bears N.60°W., 56.3', mkd: T28S R5W S25 ¼S BT.
32" D.Fir, bears S.38°E., 24.0', mkd: T28S R4W S30 ¼S BT.

BLM resurvey by Bedell & Peterson, under Group #1425 - Survey April 1988 - April 1990 (DCSO records, Vol. 49 Page 18694)

Cor. as perpetuated & recorded by Bruce Shaner, LS #430 in 1964, monumented with an iron rod, 5/8" dia., firmly set, projecting 3" above ground.
from which the remains of an original bearing tree
A rotted and burnt madrone stump, 26" dia., bears S.75°W., 15 lks. dist., no marks visible on a burned out blaze.
and the remains of the bearing trees mkd. by Shaner
A sawed and burnt fir stump 39" dia., bears S.41½°E., 38½ lks. dist., with scribe mark S visible on a burned blaze.
A root hole, bears N.56°W., 18 lks. dist., with a down fir alongside, 22" dia., with a burned blaze.
At the corner point
Set a Iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, directly over the iron rod, with brass cap mkd:
T 28 S
R 5 W R 4 W
¼
S 25 S 30
1988

(Cont. Next Page)

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 30; Sec. 25 of T28-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which new bearing trees
A Fir 14" dia., bears N.3½°E., 77 lks. dist
mkd. S30 BT.
A Fir 6" dia., bears N.29°W., 33 lks. dist., mkd.
¼ S25 BT.

