

PRIMARY CORNER DESCRIPTION W 1/16 N. line Sec. 6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

C.C. Boyer, Deputy Co. Surveyor, June, 1913 For: L. Hatfield  
Volume 2 Page 178 - F.B. 35 Pages 3-11

-----  
Set post 4x4x36 mkd: CS 1/16 S, from which:  
A R.Fir, 10" dia., bears S.57°W., 45 lks., mkd: CS 1/16 S  
BT.  
A R.Fir, 26" dia., bears S.17°E., 85 lks., mkd: CS 1/16 S  
BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 1/5/2000 - C.S. File 66/14-2

-----  
Perpetuated corner set in 1913  
Found - 3/4" I.D. iron pipe protrudes 11" above ground  
possibly set in 1927 C.S. 1/64 (Note: map in file  
shows a double circle but doesn't say if corner  
is found or set. DCSO jc 1/25/2000)  
10" now 21" 3 ft. high rotted D.Fir stump, scribing  
Fd. "CS" bears S.57°W., 29.7 ft. 1913  
26" now 26" 2½ ft. high rotted D.Fir stump, bark  
scribing visible "1/1", bears S.17°E., 54.8 ft.  
(Rec. S.17°E., 56.1 ft.) 1913  
New BTs- 19" dia., W.Fir single blazed low & scribed "X CS  
BT" bears N.72°E., 36.9 ft.  
16" dia., D.Fir single blazed low & scribed "X CS  
BT" bears S.57°W., 33.9 ft.

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause  
- 3/17/2008 - C.S. File 67/25-34

-----  
Fd. ¾" ID iron pipe, 2 live BTs & 2 BT stumps as per DCSO  
2000 rec.