

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 140340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by George M. Winter & A Bert Skeesick, Cadastral Surveyors, under Group No. 2729, surveyed Nov. 2013/Oct. 2014 - (DCSO records Vol. 58 page(s) 23239)

-----

Point for the center ¼ sec. cor. of sec. 19, at intersection of the N-S and E-W centerlines of sec. 19.  
Set a stainless steel post, 28" long, 2½" dia., 16" in the ground, in a mound of stone, 2½ ft. dia. base, to top, with brass cap mkd.

T28S R4W  
C ¼ S19  
2014

from which

A pine, 12" dia., bears N.62½°E., 63.4 ft., mkd. C¼ S19 BT  
A pine, 6" dia., bears S.31¼°E., 13.9 ft., mkd. X BT.  
Each new bearing tree has a 2½"x¼" magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

Deposit a magnet in a white plastic case at the base of the stainless steel post.  
From the corner  
E., 55 ft., to a wire fence, meandering N. and S.