

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 and 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Page 5640)

Set Fir post for ¼ sec. cor. from which
A Fir 10" dia., bears N.70°E., 250 lks. dist.
A Fir 24" dia., bears S.14°W., 60 lks. dist.

BLM resurvey by G Steven Popken, under Group #837 dated May 21, 1974 - Survey June/July 1974 (DCSO records, Vol 37 Pg 15367)

The ¼ sec. cor. of secs. 18 and 19 determined at record bearing and distance from the remains of the original BT:

A sawed Fir stump 43" dia., bears S.14°W., 60 lks. dist., with scribe mark S visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd: T 28 S R 4 W

¼ $\frac{S\ 18}{S\ 19}$
1974

from which

A Fir 6" dia., bears N.38°E., 19 lks. dist., mkd. ¼ S18 BT
A Fir 6" dia., bears S.72½°W., 15 lks. dist., mkd ¼ S19 BT

BLM resurvey by George M. Winter & A Bert Skeesick, Cadastral Surveyors, under Group No. 2729, surveyed Nov. 2013/Oct. 2014 - (DCSO records Vol. 58 page(s) 23237)

The ¼ sec. cor. of secs. 18 and 19, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree

A sawed, decayed fir stump, 40" dia., bears S.14°W., 39.6 ft., with a healed blaze.

and bearing trees mkd. by Popken in 1974

A fir, 19" dia., bears N.38°E., 12.5 ft., with a healed blaze.

A fir, 20" dia., bears S.72½°W., 9.9 ft., with a healed blaze.