

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Page 5641)

Set Willow Post, from which
A Fir 24" dia., bears N.60°E., 28 lks. dist.
A Fir 30" dia., bears S.80°W., 40 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey - July 6, 1961 - C.S. File 49/67-8

Found - Both original BTs. Each is bark scribed "¼" and each checks bearing and distance.
Find 1¼" I.P. at corner and fences. (See CS file for sketch)
New BT - 7" R.Fir bears S.42°E., 25.9 ft. scribed ¼ S18 CSBT.
Rescribe-Now 36" R.Fir N.65°E., 20.5 ft. "¼ S7 CSBT". New scribing low, near base of bearing tree.

BLM resurvey by G Steven Popken under Group #837 dated May 21, 1974 - Survey, June/July 1974 (DCSO records, Vol 37 Pg 15370)

Found 1/4 sec. cor. of secs. 7 and 18, perpetuated and recorded by the County Surveyor in 1961, monumented with an iron pipe, 1" dia., firmly set, projecting 8" above ground, from which the remains of the original bearing trees:
A Fir 35" dia., bears N.60°E., 28 lks. with scribe marks S18 BT visible on open blaze. This tree was rescribed by the County Surveyor.
and a bearing tree mkd. by the County Surveyor
A Fir 11" dia bears S.42°E. 40 lks with healed double blaze
At the corner point
Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd: T 28 S R 4 W
1/4 $\frac{S 7}{S 18}$
1974
Reset iron pipe alongside iron post.

Marc Brittain - For: Weekly & Packham - 10/2015 - M171-4

Found - 3¼" brass cap on 2½" iron pipe (+.7 above ground) (properly mkd)
Located S.60°W., 20.7' from 36" D.Fir snag with blaze and reference tag.
Located N.42°W., 26.2' from 22" D.Fir per record with blaze and reference tag.

continued next page

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Adam DeGroot - For: Weekly - Mar. 2020 - M176-63

Found - A 2½" USBLM I.P. by Popken in 1974 per firmly set & projecting 10" above ground, with a 3 1/4" brass cap properly mkd. per the record.

From which the remains of an original 1881 BT:

A 40" D.Fir snag bears N.63°E., 20.7 ft, with healed low blaze (N.60°E., 28 LKS) 1881 & 1974 (N.65°E., 20.5') 1961

And a BT by DCSO in 1961:

A 23" D.Fir bears S.43°45'E., 25.8 ft w/ healed dbl blaze (S.42°E., 25.9') 1961 (S.42°E., 40 lks) 1974

New BTs- A 14" Madrone bears N.46°45'E., 16.4 ft bark scribed "¼ S7 BT"

A 20" D.Fir bears S.34°15'W., 34.9 ft scribed "¼ S18 BT" on dbl blaze

A 10" D.Fir bears N.71°45'W., 17.3 ft scribed "¼ S7 BT" on dbl blaze

Note - Corner falls ±4.5 ft South of an E-W fence line, and ±20 ft South of a E-W cat road