TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 6 and 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Page 5643)

Set Oak Post for ¼ sec. cor., from which
An Oak 18" dia., bears N.17°W., 20 lks.
An Oak 5" dia., bears S.35°W., 40 lks.

C.C. Boyer, Deputy Co. Surveyor - For: L. Hatfield - June, 1913 - Vol. 2 Pg. 175; Field Book 35 Pgs. 3-11

Set Post for ¼ sec. cor. 4 x 4 x 36 mkd. C.S. ¼ S.6 S.7, from which
A R.Fir 36" dia., mkd. C.S. ¼ S. S.6 BT, bears N.50½°E., 21½ lks.
A R.Fir 48" dia., mkd. C.S. ¼ S. S.7 BT, bears S.83°W., 49 lks.

BLM resurvey by Rogers and Bishop, under Group #1206 - Survey, July/Aug. 1984 (DCSO records, Vol. 47 Page 17987)

Point for the ¼ sec. cor., at proportionate dist; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd: T 28 S R 4 W

¼ S 6 / S 7

1984

from which
A Fir 9" dia., bears N.86½°E., 13 lks. dist., mkd. ¼ S6 BT.
A Fir 10" dia., bears S.3½°E., 37 lks. dist., mkd. ¼ S7 BT.