

PRIMARY CORNER DESCRIPTION CS 1/16 Sec. 6

Alias	Description
Alias	Description
Alias	Description
Alias	Description

C.C. Boyer, Deputy Co. Surveyor, June, 1913 For: L. Hatfield
Volume 2 Page 176 - F.B. 35 Pages 3-11

Marked a R.Fir, 10" dia., marked CS 1/16 S for corner, from
which:

- A W.Fir, 14" dia., mkd CS 1/16 S BT bears S.58½°W., 17 lks
- A R.Fir 12" dia., mkd CS 1/16 S BT bears N.33 3/4°W., 14½ lks.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 1/11/2000 - C.S. File 66/14-1

From 1913 Vol. 2 Page 176

Found - 10" now 12" dia., D.Fir snag has healed blazes on
four sides no scribing found. (1913 Cor.)

14" now 18" dia., 2½ ft. high rotted W.Fir stump
w/scribing "T" bears S.58½°W., 11.2 ft. (1913 BT)

12" now 20" dia., 3 ft. high rotted D.Fir stump with
scribing "BT" bears N.33 3/4°W., 9.6' (1913 BT)

Set - 5/8" x 30" long iron rod in roots along east base of
corner tree with DCSO yellow plastic cap,
protrudes 8" out of base.

16" Madrone single blazed low, scribed "X CS BT"
bears S.45½°E., 21.0 ft.

10" D.Fir single blazed low, scribed "X CS BT" bears
S.10½°W., 36.3 ft.

Note - Corner falls in old partially down fence line that
runs west from corner tree. A newer fence corner
with fence lines running north & east bears
N.83°E., 22 ft. from corner tree.