

PRIMARY CORNER DESCRIPTION 1/4 Cor. between Sec. 30|29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13, Pg. 5638)

Set Oak post for ¼ sec. cor. from which:
A B.Oak 15" dia. bears N.62°W., 40 lks. dist.
A Laurel, 15" dia. bears S.75°E., . 30 lks. dist.

Doug. County Surveyors Office - G.G. Stewart. Witnesses: Frank Beck, G.A. Copeland, O.E. Leighton. Nov. 1, 1922. Vol. 3, Pg. 127 & C.S. File no. 5/27.

Found - One original BT and one stump. Bearing check with field notes except that trees are interchanged. One field note distance is given as 4 links but checks with 40 links.
Set - Square post and marked the following trees:
Yellow Pine, 30" dia. bears S.34°E., 30.2'.
Cedar, 14" dia. bears S.15½°W., 43.0'.

B.A. Shaner, for: Paul B. Hult Lbr. Co. July 1964. M22-57 & C.S. File no. 51/296.

Found - 20" Cedar BT stump (1922) scribes visible, bears S.15½°W., 43.0'.
Remains of Pine BT stump (1922) bears S.34°E. 30.2'
Set - 5/8" Iron Rod from which:
New BTS - 20" D.Fir, bears N.64°W., 109.0' mkd: S30 ¼S BT.
12" D.Fir, bears N.65°E., 49.7' mkd: S29 ¼S BT.

Howard Johnstone, for: Roseburg Resources Co 2/1986 -M 100-36

Found - 5/8" Iron Rod (1964)
Fd. BTs - 30" Pine, bears S.34°E., 30.2'. Now stump.
20" Cedar stump, bears S.15½°W., 43.0'.
24" Fir, bears N.64°W., 109.0', healed blaze.
17" Fir, bears N.65°E., 49.7', healed blaze.
Set - Aluminum cap marked 'LS 498' on existing Iron Rod.

BLM resurvey by George M. Winter & A Bert Skeesick, Cadastral Surveyors, under Group No. 2729, surveyed Nov. 2013/Oct. 2014 - (DCSO records Vol. 58 page(s) 23235)

The ¼ sec. cor. of secs. 29 and 30, perpetuated by Stewart, in 1922, by Shaner, in 1964, and by Johnstone, in 1986, from original evidence no longer in existence, monumented with an iron rod, 5/8" dia., firmly set, projecting 2" above ground, with an aluminum cap (properly) mkd. continued next page

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of bearing trees mkd. by Shaner
A burnt, decayed fir snag, 20" dia., bears N.65¼°E., 49.9
ft., with a healed blaze.
A burnt, decayed fir snag, 24" dia., bears N.63¾°W., 109.3
ft., with a healed blaze.
and new bearing trees
A madrone, 6" dia., bears N.20°E., 8.9 ft., mkd. ¼ S29 BT.
A fir, 8" dia., bears N.83½°W., 15.3 ft., mkd. ¼ S30 BT.

Each new bearing tree has a 2½"x¼" magnetic nail (Mag Nail)
driven at the base on right side center, unless otherwise
noted in the corner description.