

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Page 5640)

-----  
Set Fir post for 1/4 sec. cor., from which  
Fir 30" dia., bears N.80°E., 19 lks.  
Fir 12" dia., bears N.30°W., 24 lks.

Doug. County Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - Aug/Sept 1961 - C.S. File 49/67-30

-----  
Found - Orig. 30" now 36" Fir, N.80°E., 12.5 ft. We open and find good scribing. Also find bark scribing "B" near base.

Orig. NW BT not found.

Set Brass cap at cor. mkd: County Surveyor's Office, 1961  
1/4 S18 | S17 T28S R4W

New BTs -Rescribe O.B.T., 36" Fir N.80°E., 13.0 ft. "1/4 S17 CS BT"  
25" R.Fir bears N.31°W., 22.6 ft. scribed "1/4 S17 CS BT"

Fd. OK, BLM survey by G. Popken under Group #837 - Survey, June/July 1974 (DCSO records, Vol. 37 Page 15368)