

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs. 5 and 6

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Page 5643)

-----  
Set  $\frac{1}{4}$  sec. cor. a Fir post, from which  
A Laurel 6" dia., bears S.14°E., 24 lks.  
A Laurel 5" dia., bears S.20°W., 26 lks.

Bureau of Land Management Survey by Lynn Roseberry, under Group #636, Survey May/June 1967 (DCSO records, Vol. 34 Pages 14197-98)

-----  
Point for the  $\frac{1}{4}$  sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap mkd: T 28 S R 4 W  
 $\frac{1}{4}$   
S 6 S 5  
1967

from which  
A Fir 16" dia., bears N.67  $\frac{3}{4}$ °E., 236 lks. dist.  
mkd.  $\frac{1}{4}$  S5 BT.  
A Madrone 9" dia., bears S.40  $\frac{3}{4}$ °E., 133 lks. dist.,  
mkd.  $\frac{1}{4}$  S6 BT.