TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Corner for Sections 17 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract #376 dated Jan. 22, 1881. (DCSO records Vol. 13 Page(s) 5639-640)

Set Laurel Post from which:
A Fir, 16 ins. diam., bears N.70°E., 17 lks.
A Fir, 20 ins. diam., bears S.17°E., 37 lks.

B.L.M. Dependent resurvey by Irving Zirpel Jr. and William W. Glenn, under special instructions dated Aug. 29, 1957. (DCSO records Vol. 29 Page(s) 12256)

Point for the ¼ sec. cor. at proportionate distance; there is no remaining evidence of the original corner.

Set - an iron post, 28" long, 2½" diam., 24" in the ground, with brass cap marked:

T28S R4W

¼ S 17 / S 20

1958

from which:

A Cedar, 7" diam., bears N.16½°W., 36½ lks. dist. scribed "¼ S17 BT"
A Fir, 10" diam., bears S.16½°E., 54½ lks. dist. scribed "¼ S20 BT"

Fd. Ok by K.DeGroot, May 1997 - M124-53

Carl Sweeden - For: Seneca Jones Timber Co. - 11/1999 - M 133-55

Found - 3¼" USBLM BC on 2½" iron pipe up 0.4'
23" D.Fir BT S.16°30'E., 35.3' (54.5 lks. rec.) scar healed & tag.
7" Cedar BT, N.16°30'W., 24.1', found 1.5' section with scribing visible laying on ground.
Set - 23" Cedars BT, N.86°E., 46.2', scribed "¼ S20 BT" with tag affixed.
5.5' galvanized steel post 1.0' east of BC, painted.