TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. Sec. 5 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, Under Contract #44 dated May 30, 1854 - (DCSO records, Volume 12 Page 5043)

Set ¼ sec. post, from which
A Laurel, 20" dia. bears S.2°E., 29 lks. dist.
A Laurel, 16" dia. bears N.50°W., 8 lks. dist.

GLO retracement by Addison R. Flint, Contract #56 dated March 1, 1855 (DCSO records, Volume 12 Page 5046)

Set ¼ sec. post, from which
A Fir 8" dia. bears S.33°E., 25 lks. dist.
A Fir 10" dia. bears N.25°E., 13 lks. dist.

GLO retracement by W.H. Byars, Contract # 376 dated Jan. 22, 1881 (DCSO records, Volume 12 Page 5069)

¼ sec. cor., bearing trees standing. Set new cor. post, as per instructions, viz:
A Fir 8" dia. bears S.33°E., 25 lks. dist.
A Fir 8" dia. bears N.25°E., 13 lks. dist.

BLM Dependent Resurvey by Lynn Roseberry under Group No. 636 Survey May/June 1967 (DCSO records, Volume 34 Page 14199)

Point for the ¼ sec. cor. of sec. 5 only, at midpoint in departure on the N. bdy. of sec. 5. Set an Iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked

¼ S 5
T 28 S R 4 W
1967

from which
A Fir 21" dia. bears S.65½°E., 95 lks. dist., mkd. ¼ S 5 BT.
A Fir 40" dia. bears S.9¾°W., 228 lks. dist. marked ¼ S 5 BT.

Fd. Ok by Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 2/10/2000 - C.S. File 66/14-21