

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract #376 dated Jan. 22, 1881. (DCSO records Vol. 13 Page(s) 5635)

Set Maple post for ¼ sec. cor. from which:
Maple, 6" dia., bears S.10°E., 23 lks.
Fir, 24" dia., bears S.60°W., 33 lks.

David Edwards - For: Seneca Jones Tbr Co - 4/2010 - M 160-56

No evidence of the orig. ¼ cor. could be found & said corner was therefore set at midpoint.

Set - 5/8"x30" steel rebar with 2½" dia., alum. cap. Stamped according to BLM manual w/"LS 2339" and "2010"
8" dia., fir scribed "¼ S9 BT" bears south 5.95 ft.
7" dia., fir scribed "¼ S8 BT" bears S.87°W., 9.15 ft.
8" dia., fir scribed "¼ S8 BT" bears N.1°W., 2.40 ft.
1" dia., iron pipe of unknown origin bears S.83°58'32"E., 18.60'

6 ft. steel post is set 2 ft. south.

BTs scribed as per 1973 BLM manual & were measured to center of tree at root crown.