

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Page 5635)

-
- Set Fir post for cor. to secs. 4, 5, 8 and 9, from which
 - Laurel 5" dia., bears N.64°E., 19 lks.
 - Fir 5" dia., bears S.70°E., 14 lks.
 - Oak 20" dia., bears S.44°W., 53 lks.
 - Oak 8" dia., bears N.40°W., 7 lks.

BLM resurvey by Zirpel and Glenn under Special Instructions dated Aug. 29, 1957 (DCSO records, Vol. 29 Page 12255)

The cor. of secs. determined at record bearing & dist from the only remaining original bearing tree and substantiated by a rotted and broken off Oak stump which bears N.40°W., 7 lks. dist. The remaining orig. BT is as follows:

A Fir 20" dia., bears S.70°E., 14 lks. dist., with faint evidence of an illegible bark scribe.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd:

T28S	R4W
S 5	S 4
S 8	S 9
1958	

from which

- A Fir 6" dia., bears N.35°45'E., 33 lks. dist., mkd. T28S R4W S4 BT.
- A Fir 27" dia., bears S.46°E., 43 lks. dist., mkd. T28S R4W S9 BT.
- A Cedar 9" dia., bears S.3°W., 119 lks. dist., mkd. T28S R4W S8 BT.
- A Fir 8" dia., bears N.60°W., 19 lks. dist., mkd. T28S R4W S5 BT.

BLM resurvey by Lynn M. Roseberry, under Group #636 Survey, May/June 1967 - (DCSO records, Vol. 34 Page 14194)

Found corner, remonumented by Zirpel & Glenn in 1958, with and iron post, 2½" dia., protruding 4" above ground, firmly set, with properly mkd. brass cap.

from which the remaining original bearing trees:

- A sawed Fir stump 10 ft. high, 21" dia., bears S.70°E., 14 lks. dist., with cruiser marks visible.
- An Oak 10" dia., bears N.5¼°W., 40½ lks. dist., with no scribe marks visible on opened and rotted upper blaze & BT visible on opened lower blaze. (Rec. N.40°W., 7 lks.) (Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

and bearing trees mkd. by Zirpel and Glenn:
A Fir 9" dia., bears N.35 3/4°E., 33 lks. dist., with a healed blaze.
An uprooted Fir 30" dia., bears S.46°E., 43 lks. dist., with scribe marks T28S R4W S9 BT visible on partially healed blaze.
A Cedar 12" dia., bears S.3°W., 119 lks. dist., w/scribe marks T28S R4W S8 BT visible on partially healed blaze.
A Fir 10" dia., bears N.60°W., 19 lks. dist., with scribe marks T28S R4W S5 BT visible on partially opened blaze.
and a new bearing tree:
A Fir 21" dia., bears S.51½°E., 95 lks. dist. mkd. T28S R4W S9 BT.
From this point, the cor. of wire fences which extend W. and S.20°E., bending to E., bears N.3°W., 33½ lks. dist.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 2/15/2000 - C.S. File 66/14-29

Found - 1958 BLM BC/IP protrudes 3" above ground.
20" rotted D.Fir snag with cruiser marks bears S.66°E., 9.2 ft. (rec. S.70°E., 9.2 ft.)
8" now 20" dia., D.Fir with a fully healed single blaze, bears N.60°W., 12.5 ft. 1958
6" now 22" dia., D.Fir with a fully healed single blaze bears N.35 3/4°E., 21.8 ft. 1958
27" now down D.Fir root hole bears S.46°E., 28.4 ft. 1958
12" now 28" dia., I.Cedar with a fully healed single blaze "Rec. S.3°W., 119 lks) not measured 1958
21" now 22" dia., 7 ft. high D.Fir stump with a fully healed single blaze bears S.51½°E., 62.7 ft. 1967
Orig. 8" now badly rotted 8" dia., 10 ft. high Oak snag shows sign of previous search faint "B" visible on low blaze. Blazes face southeast. Tree ready to fall over **set a 5/8" by 30" long iron rod with alum cap** near center of BT, protrudes 5" out of SE base. This old BT & set IR bears N.5¼°W., 26.7 ft. from 1958 BLM BC/IP.
Corner position determined by 1881 rec. "N.40°W., 4.6 ft." is near an old fence corner with fences extending East - West and S.25°E, bears S.45°W., 2.5 ft. from corner position determined by old Oak BT.

No other OBTs found. See last Pg for pictures.

continued next page

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Fd. Ok by M. Smalley 5/9/2006 - C.S. File 65/60-7

David Edwards - For: Seneca Jones Tbr Co - 4/2010 - M 160-56

Found - Brass cap
24" Cedar bears S.3°W., 78.5' Both w/healed blaze.
20" Fir bears N.60°W., 12.5'
New BT - 7" dia., fir bears N.1°W., 9.95 ft. scribed "T28S
R4W S5 BT"
Set 6 ft. steel post 2' north.

FD. as per M160-56 by D Edwards, 11/2014 - M168-67

