

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Corner for Sections 28 & 33.

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13, Pg. 5632).

Set Fir post for ¼ Sec. Cor. from which:
A Fir, 36" dia. bears North 21 lks. dist.
A Fir, 6" dia. bears South 8 lks. dist.

Doug. County Surveyors Office - G.G. Stewart Deputy. Witnesses Frank Evans, H. Stimpson, C.Crocker. Feb. 1922. C.S. File 5/27; M 2-4 & Vol. 3, Pg. 113.

Found - 44" Fir that had blaze mark in bark but had been burned badly. 20' south was stump hole of small tree. I measured to top of hill from this tree and it was 450+ ft. so I assumed the tree to be an original BT.
Set A 1" Iron Pipe for corner and marked the following trees:
Fir, 44" dia. bears N.30°E., 14.0'
W.Fir, 24" dia. bears S.28½°W., 73.0'

BLM Resurvey; Zirpel & Glenn. Under special instructions dated Aug. 29, 1957. (DCSO records Vol. 29, Pg. 12248)

The ¼ sec. cor. of secs. 28 & 33, perpetuated & record by Stewart in 1922, at record bearing and distance from the remains of the orig. BTs; which no longer exist, monumented with an iron pipe, 1" dia., firmly set, 8" above ground; from which BTs by Stewart in 1922

A Fir, 51" dia. bears N.30°E., 21 lks. with scribe marks
¼S CS BT visible on bark blaze.

A W.Fir, 33" dia bears S.28½°W. 111 lks with healed blaze and local BT of which I have no record

A Cedar, 7" dia. bears N.9½°E., 32 lks. with scribe marks
¼ S28 visible on open blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 26" in the ground, with brass cap marked:

T28S R4W
¼ $\frac{S\ 28}{S\ 33}$

Reset iron pipe alongside iron post.

Greg Lang - For: McDonald & Seneca Jones Tmbr Co. 2/2016 - M170-58

Found - brass cap
New - 10" D.Fir bears N.25¾°W., 45.30', scribed ¼ S28 BT
continued next page

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Corner for Sections 28 & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

15½" cedar bears N.55½°E., 29.35', scribed ¼ S18 BT 13" D.Fir bears S.13°E., 2.15' - scribed ¼ S33 BT Existing 38" W.Fir bears S.27°W., 73.0' (S.28½°W., 73.26' per 1957 BLM)
Fd as per M170-58; a steel post is fd S.88°W 1.0 ft by D Edwards - 7/2022 - C.S. File 65/110-4