

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 16 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Page 5634)

Set Laurel post for ¼ sec. cor. from which
A Laurel 12" dia., bears N.10°E., 60 lks.
A Laurel 20" dia., bears S.20°W., 48 lks.

BLM resurvey by Zirpel and Glenn under Special Instructions dated Aug. 29, 1957 (DCSO records, Vol. 29 Page 12252)

The ¼ sec. cor., determined at record distance from the two original bearing trees as follows:

A Madrone 26" dia., bears N.25°E., 60 lks. dist., with illegible scribe marks visible on a partially opened blaze. (Rec. N.10°E.)
A Madrone 31" dia., bears S.18°W., 48 lks. dist., with faint scribe marks visible on a partially opened blaze. Rec. S.20°W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd:

T28S R4W
¼ S 16
S 21
1958

from which

A Fir 13" dia., bears N.25°E., 27½ lks., mkd. ¼ S16 BT.
A W.Fir 8" dia., bears S.13°W., 65 lks., mkd. ¼ S21 BT.

BLM resurvey by George M. Winter & A Bert Skeesick, Cadastral Surveyors, under Group No. 2729, surveyed Nov. 2013/Oct. 2014 - (DCSO records Vol. 58 page(s) 23233-4)

The ¼ sec. cor. of secs. 16 and 21, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A decayed madrone stump, size indeterminate, bears N.27°E., 39.6 ft., with no marks visible.

A madrone snag, 33" dia., bears S.14½°W., 31.7 ft., with a hollowed blaze. (Record, S.18°W.)

and the remains of a BT mkd. by Zirpel and Glenn in 1958

A fir stump, 14" dia., bears N.25°E., 18.2 ft., with no marks visible.

A roothole bears S.13°W., 42.9 ft., with fallen fir trunk, 15" dia., lying alongside, with no marks visible.

and new bearing trees

A fir, 9" dia., bears N.66½°E., 15.7 ft., mkd. T28S R4W S16 BT. continued next page

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 16 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A fir, 11" dia., bears S.16¼° E., 30.2 ft., mkd. T28S R4W S21 BT.

Each new bearing tree has a 2½"x¼" magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position in NAD 1983 (2011) of the following corners as determined by direct GPS observations or ties to temporary GPS points, utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS):

Latitude: 43°07'38.25" N Longitude: 123°10'39.01" W

Ken Hoffine - Crew: Gary Angiolet and Jake Furgerson - For: Lone Rock Timber Co - Feb. 2020 - C.S. File 65/104-36

Found - 1958 BLM BCIP per Vol. 58 pgs. 23233-4
10" D.Fir bears N.66½°E., 15.7 ft. (record N.66½°E., 15.7 ft from 2014 BLM field notes Vol.58 pgs. 23233-4) healed face and tag
11" D.Fir bears S.16¾°E., 30.2 ft. (record S.16¾°E., 30.2 ft from 2014 BLM field notes Vol. 58 PGS. 23233-4) healed face and tag
New - 9" Cedar bears N.53°W., 29.3 ft. We scribe T28S R4W ¼ S16 BT and tag tree.
18" D.Fir bears S.38¾°W., 9.8 ft. We scribe T28S R4W ¼ S21 BT and tag tree
Note - FD 1958 BLM BCIP 0.3 ft. above ground level. Monument lies approx. 40 ft. South of old grown over skid road, on SW facing slope.