

PRIMARY CORNER DESCRIPTION 1/4 Corner for Sections 4 and 9

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>Original - W.H. Byars, under contract #376 dated Jan. 22, 1881. (DCSO records Vol. 13 Page(s) 5635-36)</p> <p>-----</p> <p>Set Fir post for ¼ sec. cor. from which: A Fir, 36" dia. bears S.25°W., 27 lks. A Fir, 12" dia. bears N.28°W., 42 lks.</p>
<p>BLM resurvey by Zirpel and Glenn under special instructions dated Aug. 29, 1957. (DCSO records Vol. 29 Page(s) 12254)</p> <p>-----</p> <p>The ¼ sec. cor. of secs. 4 and 9, determined at record distance from the two original bearing trees, as follows: A Fir, 34" dia. bears N.29°W., 42 lks. dist., bark scribed ¼S BT. (rec. bearing N.28°W.) A Fir, 50" dia. bears S.27½°W., 27 lks. dist., bark scribed ¼S BT. (rec. bearing S.25°W.)</p> <p>Set - at the corner point set an iron post, 28" long, 2½" dia. 20" in the ground, and in a mound of stone, 2 ft. base to top, with brass cap marked: T28S R4W ¼ $\frac{S}{S} \frac{4}{9}$</p> <p>New BT - A Fir, 21" dia. bears S.5°W., 64 lks. dist. mkd. ¼ S9 BT.</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 2/15/2000 - C.S. File 66/14-28</p> <p>-----</p> <p>Found - 1958 BLM BC/IP, protrudes 12" above ground. 36" now 50" dia., 6 ft. high D.Fir stump w/faint bark scribed line bears S.27½°W., 17.8 ft. OBT 12" now 34" dia. 6 ft. high D.Fir stump with bark scribing "¼S" bears N.29°w., 27.7 ft. OBT 21" now 24" dia. 6 ft. high D.Fir stump with a fully healed single blaze bears S.5°W., 43.5 ft. (rec. S.5°W., 42.2 ft)</p> <p>New - 16" dia., I.Cedar double blazed & scribed "¼ S9 CS BT" bears S.9°W., 35.00 ft. 8" dia. Dogwood double blazed & scribed "¼ S4 CS BT" bears North, 13.5 ft. 4" dia., D.Fir double blazed & scribed "X CS BT" bears N.60°W., 7.0 ft. 15" dia., I.Cedar double blazed & scribed "¼ S9 CS BT" bears S.69°E., 19.8 ft.</p>
<p>Fd. corner as per DCSO 2000 renewal by D.Edwards 4/2010 - M160-56</p>