

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 4; & 33 of T. 27-4

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 12 Page 5047)

Set 1/4 sec. post, from which
(Witness trees to 1/4 post)
A Laurel, 16" dia. bears N.2°E., 10 lks. dist.
A B.Oak 4" dia. bears S.45°W., 11 lks. dist.

GL0 survey by W.H. Byars, Deputy Surveyor under contract
#376 dated January 22, 1881 (DCSO records, Volume 12 Page
5080

Qr. Sec. cor., set new post as per instructions, bearing trees
standing, viz:
A Laurel, 16" dia. bears N.2°E., 10 lks. dist.
A B.Oak 4" dia. bears S.45°W., 11 lks. dist.

F.C. Frear, Deputy For: Ingram & Adams, Dec. 11-13, 1918
Volume 3 Page 45 and C.S. File 4/34

Renewed from old Govt BT.
Set 3/4" x 48" Galv. iron pipe, from which
14" Fir bears N.42 1/4°E., 1.83 chs.
14" Fir bears N.32 1/4°W., 1.065 chs.

James W. Byron, Deputy; Dale McFarland; Jim Powell - Sept.
14, 1961 - C.S. File 49/67-32

Found - 3/4" I.P. at corner & under E-W fence. We also find
both BTs as recorded by Frear, 1918. We open
NW BT & find good scribe marks. Both BTs, now
stumps.
New BTs - 8" R.Fir bears N.16 1/2°E., 75.7 ft. scribed 1/4 S33 CSBT
9" Laurel bears N.23 1/2°W., 45.5 ft. scribed 1/4 S33
CS BT.
No trees near to South.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 2/7/2000 - C.S. File 66/14-19

Found - 3/4" O.D. iron pipe protrudes 6" above ground. 1918
No OBTs found.
14" now 25" dia., 2 1/2 ft. high D.Fir stump scribing
found "BT" bears N.32 1/4°W., 70.3 ft. 1918
14" now 30" dia. 2 ft. high D.Fir stump scribing
found "BT" bears N.42 1/4°E., 120.8 ft. 1918
continued next page

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs 4; & 33 T27-4

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

8" now 21" dia., with a fully healed blaze, bears N.16½°E., 75.7 ft. 1961
9" now 15" dia., Madrone with a fully healed blaze bears N.25°W., 45.5 ft. (rec. N.23½°W., 45.5 ft.) 1961
New BT - 10" dia., W.Oak double blazed & scribed "¼ S33 CS BT" bears N.86½°E., 57.1 ft.
No trees reasonable to south.
Corner lies in old E-W fence line near old down barn.