

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 360200

PRIMARY CORNER DESCRIPTION E 1/16 Secs. 28 & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Resurvey; Zirpel & Glenn. Under special instructions dated Aug. 29, 1957. (DCSO records Vol. 29, Pg. 12247-8)

Point for E 1/16 sec. cor. of secs. 28 & 33, established and recorded by J.H. Markham, monumented with an iron pipe, 2" dia., firmly set, 2" above ground, from which Markham's BTs:
A madrone, 10" dia., bears N.1¼°W., 19 lks., with scribe marks 1/16 S BT visible on bark.
A maple, 7" dia., bears S.3°W., 15 lks., with scribe marks 1/16 S 2880 BT on bark.

At the corner point
Set an iron post, 28" long, 2½" dia., 26" in the ground, with brass cap marked:

E 1/16 $\frac{S\ 28}{S\ 33}$
1958

from which new BTs
A hemlock, 9" dia., bears N.37¼°E., 25 lks., mkd: E 1/16 S28 BT.
A fir, 14" dia., bears S.10°E., 48 lks., mkd: E 1/16 S33 BT.
Reset iron pipe alongside iron post.

Douglas Co. Surveyors Office - Stephen J. Flauser - Mike Koch - 11/2/2012 - C.S. File 67/36-45

CONDITION REPORT ONLY
1958 monument fd as described.
All accessories fd as described in 1958
All BTs re-tagged and flagged.