

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by George M. Winter & A Bert Skeesick, Cadastral Surveyors, under Group No. 2729, surveyed Nov. 2013/Oct. 2014 - (DCSO records Vol. 58 page(s) 23230)

The ¼ sec. cor. of secs. 21 and 22, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which the remains of BTs mkd. by Zirpel & Glenn in 1958

A fir, 16" dia., bears S.87°E., 38.9 ft., with a healed blaze.

A roothole bears S.66°W., 21.1 ft., with fallen, decayed fir trunk, 16" dia., lying alongside, with a healed blaze.

and a new bearing tree

A fir, 7" dia., bears S.38¼°W., 31.4 ft., mkd. ¼ S21 BT. Each new bearing tree has a 2½"x¼" magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

From this cor., a point established by Markham, in 1950, bears N.35°41'W., 58.1 ft., monumented with an iron pipe, 1½" dia., firmly set, projecting 12" above ground, and is not utilized in the course of this survey.