

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Page 5628)

Set Cedar post for cor. to secs. 15, 16, 21 and 22, from which

- Maple 8" dia., bears N.86°E., 19 lks.
- Fir 18" dia., bears S.38°E., 19 lks.
- Cedar 10" dia., bears S.88°W., 40 lks.
- Fir 10" dia., bears N.10°W., 17 lks.

John Markham, Engineer - V.C. Dunnivan; Geo. & Wm. Vaughn, Witnesses - June 21, 1950 - C.S. File 40/257-2

Determined from remains of O.B.T., a dead Cedar windfall S.88°W., 26.0 ft. dist. Scribe legible.

- A W.Fir N.15°W., 16.0 ft. dist. I remark S 16.
- A 30" W.Fir S.38°E., 21.0 ft. dist. I remark S 22.

At corner point, Set 3/4" x 30" I.P. 20" in ground, from which

- A Cedar 4" dia., bears N.72°E., 9.5 ft. mkd. S15 2880 BT.
- A Cedar 12" dia., bears S.83°W., 41.0 ft. mkd. S21 2880 BT

BLM resurvey by Zirpel and Glenn under Special Instructions dated Aug. 29, 1957 (DCSO records, Vol. 29 Pages 12238-39)

The sec. cor. perpetuated and recorded by Markham in 1950, at record bearing and distance from the orig. SW BT and monumented with an I.P. 1½" dia., firmly set, 8" above ground, from which the orig. BT:

- A Cedar snag, deand and fallen, 18" dia., bears S.88°W., 40 lks. dist., with illegible scribe marks visible on an open face.

and locally established bearing trees:

- A Cedar 5" dia., bears N.74°E., 14 lks. dist., mkd. 2880 S22 on an unhealed blaze.
- A sawed Hemlock stump 30" dia., bears S.38°E., 34 lks. dist., mkd. S21 on unhealed blaze.
- A Cedar 15" dia., bears N.83°W., 60 lks. dist., mkd. S21 2880 BT on unhealed blaze.
- A Fir snag 16" dia., bears N.14°45'W., 26 lks. dist. mkd. S16.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T28S R4W	
S 16	S 15
S 21	S 22
1958	

from which (Cont. Next Page)

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. 15, 16, 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 8" dia., bears N.27°45'E., 66 lks. dist., mkd.
T28S R4W S15 BT.
A Hemlock 7" dia., bears S.29½°E., 44½ lks. dist., mkd.
mkd. T28S R4W S22 BT.
A W.Fir 21" dia., bears S.84½°W., 73 lks. dist., mkd.
T28S R4W S21 BT.
A Fir 25" dia., bears N.50°45'W., 73 lks. dist., mkd.
T28S R4W S16 BT.
Deposit iron pipe alongside iron post.

BLM resurvey by George M. Winter & A Bert Skeesick, Cadastral Surveyors, under Group No. 2729, surveyed Nov. 2013/Oct. 2014 - (DCSO records Vol. 58 page(s) 23230-1)

The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2½" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd.
from which the remains of a BT mkd. by Zirpel & Glenn in 1958
A hollowed, decayed fir, 27" dia., bears N.50¾°W., 48.2 ft., with a hollow blaze.
and new bearing trees
A fir, 10" dia., bears N.30½°E., 46.8 ft., mkd. T28S R4W S15 BT
A hemlock, 17" dia., bears S.38¾°E., 42.0 ft., mkd. T28S R4W S22 BT.
A hemlock, 15" dia., bears S.33½°W., 17.5 ft., mkd. T28S R4W S21 BT.
A fir, 9" dia., bears N.56½°W., 39.8 ft., mkd. T28S R4W S16 BT.
An iron pipe 1¼" dia., firmly set, projecting 7" above ground is alongside the cor.
Each new bearing tree has a 2½"x¼" magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.