

PRIMARY CORNER DESCRIPTION Sec. cor. for 9, 10, 15 and 16

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Page 5629)

Set Laurel post for cor. to secs. 9, 10, 15 & 16, from which
Fir 18" dia., bears N.14°E., 126 lks.
Fir 40" dia., bears S.15°E., 179 lks.
Laurel 10" dia., bears S.22°W., 56 lks.
Laurel 12" dia., bears N.45°W., 76 lks.

BLM resurvey by Zirpel and Glenn under Special Instructions dated Aug. 29, 1957 (DCSO records, Vol. 29 Page 12240)

Point for the secs. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd:
T28S R4W
S 9 | S 10
S 16 | S 15
1958

from which
A Fir 9" dia. bears N.17°E., 94½ lks. mkd. T28S R4W S10 BT
A Fir 13" dia. bears S.22°E., 80 lks. mkd. T28S R4W S15 BT
A Cedar 11" dia. bears S.39°W. 69 lks mkd. T28S R4W S16 BT
A Fir 13" dia., bears N.36°W. 73½ lks. mkd. T28S R4W S9 BT

Ronald Geisler, L.S. #1988, for: Champion International
May 1985 - M 98-72

Found - 1958 BLM brass cap.
14" Fir bears S.22°E., 52.5 ft. (Rec. 52.8 ft.)
closed face.
19" Fir stump, 3 ft. tall, bears N.36°W., 48.5 ft.
Closed face.
15" Fir bears N.17°E., 62.4 ft. Closed face.
SW Cedar BT not found.
New BTs - 5" Fir bears S.71°W., 34.9 ft. scribed "X BT"
12" Fir bears N.20°W. 18.1 ft scribed T28S R4W S9 BT

David Edwards - For: Seneca Jones Tbr Co - 4/2010 - M 160-56

Found - Brass cap.
All previous BTs gone.
New BTs- 7" dia., Fir bears S.55°E., 6.60 ft. scribed "T28S R4W S15 BT"
4" dia., Fir bears S.0°30'W., 6.0 ft. scribed "T28S R4W S16 BT"
Set 6 ft. posts 2 ft. west & 2 ft. east.