

TOWNSHIP 28 RANGE 04W POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor for Sec 34; & Sec 3 T 29-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, Contract # 44 dated May 30, 1854.
(DCSO records Vol. 13, Pg. 5607)

Set 1/4 Sec. post at proper dist. from which:
A Laurel, 12" dia. bears N.30°E., 27 lks. dist.

South boundary of T.28-4, surveyed by W.H. Byars, Contract #376, dated Jan. 22 1881. (DCSO records Vol. 13 Pg. 5614)

Set Maple post for ¼ sec. cor. from which:
A Fir, 8" dia. bears S.1°W., 33 lks. dist.
A Fir, 30" dia. bears N.80°W., 35 lks. dist.
Note: Per note in Byars 1881 survey "In the execution of this work I found that the old line established for the S bdy of this Township was glaringly at fault..." Byars set his own corners. See CS 63/166 BLM opinion file T28-4 (added 4/7/2010)

G.G. Stewart, Deputy Co. Surveyor, & Frank Evans, Stimpson, C. Crocker. Feb. 8-16 1922; M 2-4.

Set - Iron Pipe from 30" original BT. Charred stump of other BT present.
New BTs - A Fir, 30" dia. bears N.80°E., 23.0 ft.
A Fir, 30" dia. bears S.22°E., 59.5 ft.

James W. Byron, Deputy Co. Surveyor, & Dale McFarland, Jim Powell - August 1961, C.S. File 49/67-20

Found - 3/4" I.P. in E.W. fence line and both BTs as Recorded by Stewart in 1922. S.E. BT shows good scribing "¼S".
New BTs - A R.Fir, 9" dia. bears N.56¼°E. 8.5 ft mkd. ¼ S34 CS BT.
A R.Fir, bears 8" dia. bears S.75°E., 21.4 ft. mkd. ¼ S3 CS BT.

Found OK by G. Lang, August 1999 - M133-18 A & B

BLM resurvey by George M. Winter, Cadastral Surveyor, under Group No. 2747, surveyed May/July 2014 - (DCSO records Vol. 58 page(s) 23195-6)

The ¼ sec. cor. of secs. 3 & 34, on the N. bdy. of the Tp., perpetuated by Stewart, in 1922, further perpetuated by Byron, in 1961, monumented with an iron pipe, 1/2" dia., firmly set, projecting 2" above ground, from which the remains of an original bearing tree continued next pg

TOWNSHIP 28 RANGE 04W POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor for Sec 34; & Sec 3 T 29-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir stump, size indeterminate, bears N.80°W., 23.1 ft., with no marks visible.
and bearing trees mkd. by Byron

A fir, 20" dia, bears N.56¼°E., 8.5 ft., with a healed blaze.

A fir, 16" dia, bears S.75°E., 21.4 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia, 22" in the ground, directly over the iron pipe, with brass cap mkd.

T28S R4W

¼ $\frac{S34}{S 3}$

T29S

2014

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located under a field fence extending E. and W.