TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Page 5629)

Set Laurel post for ¼ sec. cor., from which
Fir 36" dia., bears N.40°E., 16 lks.
Laurel 6" dia.,bears S.5°W., 25 lks.

BLM resurvey by Zirpel and Glenn under Special Instructions dated Aug. 29, 1957 (DCSO records, Vol. 29 Page 12241)

Point for the ¼ sec. cor.,at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd: T28S R4W

¼ S 10 / S 15

1958

from which
A Fir 10" dia., bears N.13¼E., 62½ lks. dist., mkd. ¼ S10 BT.
A Fir 28" dia., bears S.38¼°W., 54 lks. dist., mkd. ¼ S15 BT.

Fd. OK, Burton Holt, October 1981, M 90-5

BLM resurvey by George M. Winter, Cadastral Surveyors, under Group No. 2704, surveyed July 2013/Feb. 2016 - (DCSO records Vol. 58 page(s) 23353)

The ¼ sec. cor. of secs. 10 and 15, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.
from which bearing trees mkd. by Zirpel and Glenn in 1958
A fir, 36" dia., bears N.13¼°E., 41.2 ft., with a healed blaze.
A fir, 40" dia., bears S.38¼°W., 35.6 ft., with a healed blaze.
The geographic position in NAD 1983 (2011)
Latitude: 43°08'28.112"N. Longitude: 123°09'29.251"W