

PRIMARY CORNER DESCRIPTION ¼ cor. Sec. 3 only (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>Original - Nathaniel Ford, Under Contract #44 dated May 30, 1854 (DCSO records, Volume 12 Page 5044) ----- Set ¼ sec. post, from which A R.Fir 18" dia. bears S.40°W., 9 lks. dist. A R.Fir 12" dia. bears N.10°W., 9 lks. dist.</p>
<p>GLO retracement by Addison R. Flint, Contract #56 dated March 1, 1855 (DCSO records, Volume 12 Page 5047) ----- Set ¼ sec. post, from which A Fir 4" dia. bears N.56°E., 18 lks. dist. A Fir 33" dia. bears S.54°E., 29 lks. dist.</p>
<p>GLO resurvey by W.H. Byars, Under Contract #376 dated Jan. 22, 1881 (DCSO records, Volume 12 Page 5080) ----- Qr. sec. post, set new post as per instructions, bearing trees all standing viz: March 9, 1881 A Fir 4" dia. bears N.56°E., 18 lks. dist. A Fir 33" dia. bears S.54°E., 29 lks. dist.</p>
<p>BLM Dependent Resurvey by Zirpel and Glenn - Under Special Instructions dated Aug. 29, 1957 (DCSO records, Volume 29 Page 12223) ----- Point for the ¼ sec. cor. of sec. 3 only, on the N. bdy. of T.28-4, at midpoint on the N. bdy. of sec. 3. Set an Iron post 28" long, 2½" diam. 26" in the ground, with brass cap marked: ¼ S 3 T28S R4W 1958 from which A Fir 13" dia. bears S.80°E., 441 lks. marked ¼ S3 BT. Raise a mound of stone, 3 ft. base, 1½ ft high south of corner</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 1/24/2000 - C.S. File 66/14-9 ----- Found - BLM BC/IP 13" now 27" dia., D.Fir with a fully healed single blaze bears S.80°E., 290.0 ft. (rec. S.80°E., 291.1 ft.) 1958 1958 BLM BC/IP S¼ S34 bears S.88½°E., 22.2 ft. New BT - 12" dia., double trunked Cedar double blazed & scribed "¼ S3 CS BT" on easterly trunk. Root crown bears S.41½°W., 271.3 ft.</p>
<p>cont. next pg</p>

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION ¼ cor. Sec. 3 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause
- 3/12/2008 - C.S. File 67/25-31

Fd. Ok as per DCSO 2000 renewal

BLM resurvey by George M. Winter, Cadastral Surveyors, under
Group No. 2704, surveyed July 2013/Feb. 2016 - (DCSO records
Vol. 58 page(s) 23351)

The ¼ sec. cor. of sec. 3 only, T.28S., R.4W., perpetuated by
Smith, Deputy Co Surveyor, in 2000, monumented with an iron
post, 2½" dia., firmly set, projecting 5" above ground, with
brass cap, orientated to the south, (properly) mkd.

from which a bearing tree mkd. by Zirpel and Glenn in 1958
A fir, 29" dia., bears S.80½°E., 290.0 ft., with a healed
blaze. (Record, S.80°E., 291.1 ft.)

and a bearing tree mkd. by Smith
A double trunked cedar, 13" dia., bears S.41½°W., 271.3
ft., with a healed double blaze.

From the corner
S., 28 ft., to a two track gravel road, bears S.44°E and
N.44°W.