

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Corner to Sections 26, 27, 34 & 35.

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13, Pg. 5621)

Set Fir post for corner from which:

- A Fir, 7" dia. bears S.45°E., 17 lks. dist.
- A Laurel, 24" dia. bears N.40°E., 56 lks. dist.
- A Laurel, 36" dia. bears S.65°W., 58 lks. dist.
- A Laurel, 10" dia. bears N.15°W., 36 lks. dist.

B.L.M. Resurvey; Zirpel & Glenn. Under special instructions dated Aug. 29, 1957. (DCSO records Vol. 29 Pg. 12230)

- Found - A rotted madrone stump, bears S.65°W., 58 lks. dist. with scribe marks BT visible in old blaze. (Orig.)
A rotted madrone stump, bears N.40°E., 56 lks. dist. with rotted blaze. (Original)
A rotted madrone stump, bears N.15°W., 36 lks. dist. no scribe marks visible. (Original)

Set - Iron post with brass cap marked:

T28S R4W
S 27 | S 26
S 34 | S 35
1958

- New BTs - A Fir, 10" dia. bears N.43°45'E., 85 lks. dist. mkd: T28S R4W S26 BT.
A Fir, 18" dia. bears S.21¼°E., 40 lks. dist. mkd: T28S R4W S35 BT.
A Cedar, 13" dia. bears S.30°W., 67 lks. dist. mkd: T28S R4W S34 BT.
A Fir, 13" dia. bears N.72¼°W., 62 lks. dist mkd: T28S R4W S27 BT.

Found OK by. R. Rice, Nov. 2002 - M141-27