

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. 22, 23, 26 and 27

| Alias | Description |
|-------|-------------|
| _____ | _____ |
| Alias | Description |
| _____ | _____ |
| Alias | Description |
| _____ | _____ |
| Alias | Description |
| _____ | _____ |

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Page 5622)

Set Cedar post for cor. to secs. 22, 23, 26, 27, from which
Fir 30" dia., bears N.30°E., 100 lks.
Fir 30" dia., bears S.89°E., 179 lks.
Fir 30" dia., bears S.32°W., 37 lks.
Fir 18" dia., bears N.77°W., 31 lks.
(G.J. Kun's house, S.25°E.)

H.L. Eppstein, Co. Surveyor - Wit: Stuer; Frank Cain; Bert Lane; Jack Morris; Thackery - April-Aug. 1935 - Vol. 4 Page 23 and C.S. File 23/1

No evidence of old corner. Set corner from double proportionate distance. Set auto housing 30" long for corner from which
Fir 16" dia., bears S.68°W., 47.7 ft. mkd. S27 CS BT.
R.Fir 16" dia., bears S.13½°E., 48.0 ft. mkd. S26 T28S R4W CS BT.
Fir 16" dia., bears N.30½°W., 55.8 ft. mkd. S22 T28 R4W CS BT.
Cedar 36" dia., bears N.39¼°E., 81.2 ft. mkd. S23 T28 R4W C.S. B.T.

Howard Johnstone, L.S. #498 for: Roseburg Resources - March 1986 - M 100-47

Found - 2" iron pipe.
26" Fir bears N.32½°W., 56.8 ft. Healed.
34" Fir bears S.65 3/4°W., 48.8 ft. Healed.
Set - 5/8" x 36" Iron rod and alum. cap in iron pipe.
New BTs -6" Fir S.26°E., 8.1 ft.
11" Fir bears N.61°E., 27.1 ft.

Found OK by K. DeGroot, July 2002 - M140-53