

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Page 5624)

Set Fir post for cor. to secs. 10, 11, 14 and 15, from which
Fir 8" dia., bears N.30°E., 43 lks.
Cedar 30" dia., bears S.40°E., 8 lks.
Cedar 24" dia., bears S.5°W., 43 lks.
Laurel, 18" dia., bears N.88°W., 69 lks.

Doug. County Surveyors Office - James Byron, Deputy - April/
May 1957 - C.S. File 47/180

Found - All original BTs and all have open face with
scribing visible except for NE BT which shows
good face. I do not open. All BTs check for
bearings and distances except NE BT, it checks
for bearing- measured distance 18.4 ft. (Record,
28.4 ft.)

Set Brass cap at cor. mkd $\frac{10}{15} | \frac{11}{14}$ T28S R4W County Surveyors
Office, 1957

Blaze and bark scribe orig. BT, now 20" Fir N.30°E., 18.4 ft.
mkd. S11 T28S 4 W CS BT.

Rescribe orig. BT, now 26", A Laurel N.88°W., 44.0 ft. mkd.
S10 T28S R4W CS BT.

Rescribe orig. BT, now 24" Cedar S.5°W., 28.4 ft. mkd. S15
T28S R4W CS BT.

Rescribe orig. BT, now 40" Cedar S.40°E., 5.3 ft. mkd. S14
T28S R4W CS BT.

BLM resurvey by Zirpel and Glenn under Special Instructions
dated Aug. 29, 1957 (DCSO records, Vol. 29 Pages 12240-41)

The Sec. cor., perpetuated and recorded by Byron, 1957, at
record bearing and dist. from three orig. BTs and at record
bearing from the fourth orig. BT, monumented with an I.P. 1"
dia., firmly set 8" above ground, with properly mkd. B.Cap.
from which the original bearing trees:

A Fir 24" dia., bears N.30°E., 29 lks. rescribed "T28S R4W
S11 CS BT. (Rec. dist. 43 lks.)

A Cedar 37" dia., bears S.40°E., 8 lks. rescribed T28S R4W
S14 CS BT.

A Cedar 20" dia., bears S.5°W., 43 lks. dist., rescribed
T28S R4W S15 CS BT.

A Madrone 24" dia., bears N.88°W., 65 lks. dist., (69 lks.
on the slope) rescribed T28S R4W S10 CS BT. (Rec. Dist.
69 lks.) (Cont. Next Page)

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

At the corner point
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T28S R4W
S 10 | S 11
S 15 | S 14
1958

from which new bearing trees
A Fir 18" dia., bears N.60°W., 37½ lks. dist., marked
T28S R4W S10 BT.
Deposit local corner material alongside iron post.

Found OK, by BLM resurvey by Bedell & Rogers, 1987-1991.
DCS0 records, Vol. 49 Page 18681)
1958 BLM brass cap; 3 orig. BTs, & 1 BT by Zirpel and Glenn
and 1957 DCS0 brass cap.

FD. Ok by David Edwards, 11/2008 - M 158-30
FD. Ok by K. DeGroot, 3/2009 - M157-11

Dan Saily, Lone Rock Timber Co. - Crew: Brett Ragon, Ignacio Roman & Trevor Clemo - 12/2023 - M183-27

Found - 1958 BLM brass cap and iron pipe (properly mkd). The monument is flush with the ground on south slope approximately 100' south of BLM rock road. A Douglas Co. brass cap and iron pipe is touching the BLM brass cap on eastern edge of cap.
Douglas Co. Surveyors Office section corner lies N.64°27'13"W., 0.17' from BLM brass cap
23" I.Cedar bears S.6¼°W., 26.9' record (S.5°W., 43 lks) with BLM tag and healed face.
23" Pacific madrone snag bears N.87°W., 42.6' record (N88°W 66 lks) with BLM tag and well healed face
26" D.Fir bears N.59°W., 24.8' record (N.60°W., 40 lks) with BLM tag and healed face.
30" D.Fir bears N.30¼° 18.1' record (N.30°E., 29 lks) with BLM tag and visible bark scribe.