

PRIMARY CORNER DESCRIPTION Sec. cor. for 2, 3, 10 and 11

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Pages 5624-25)

Set Cedar post for cor. to secs. 2, 3, 10 and 11, from which
 Cedar 8" dia., bears N.50°E., 30 lks.
 Fir 10" dia., bears S.42°E., 36 lks.
 Fir 36" dia., bears S.20°W., 45 lks.
 Fir 16" dia., bears N.40°W., 7 lks.

BLM resurvey by Zirpel and Glenn under Special Instructions dated Aug. 29, 1957 (DCSO records, Vol. 29 Pages 12244-45)

The Sec. cor. determined at record distance from the faces of four original bearing trees, as follows:
 Cedar snag 9" dia., bears N.56¼°E., 31 lks. dist., scribed T28S R4W. (Rec. N.50°E., 30 lks.)
 Fir 22" dia., bears S.32°E., 37½ lks. dist., bark scribed S11 T28S R4W BT. (Rec. S.42°E., 36 lks.)
 Fir 32" dia., bears S.28¼°W., 47½ lks. dist., bark scribed S10 T28S R4W (Rec. S20°W., 45 lks.)
 Fir 24" dia., bears N.40°W., 8½ lks. dist., bark scribed T28S R4W BT. (Rec. distance, 7 lks.)

At the corner point
 Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd:

| | |
|----------|------|
| T28S R4W | |
| S 3 | S 2 |
| S 10 | S 11 |
| 1958 | |

from which
 A Cedar 13" dia., bears N.20°45'E., 144½ lks. dist., mkd. T28S R4W S2 BT.
 A Fir 30" dia., bears N.51°45'W., 43 lks. dist., marked T28S R4W S3 BT.

Doug. County Surveyors Office - M.E. Godfrey & Crew - June 5, 1964 - C.S. File 49/67-39

Found - GLO brass cap set in 1958 survey.
 24" Fir snag N.40°W., 5.6 ft. bark scribed.
 13" Cedar snag N.20 3/4°E., 95.4 ft. all scribing visible.
 All other BTs are blown down, logged or gone.
 New BTs -12" D.Fir S.41°E., 57.6 ft. mkd. T28S R4W S11 CS BT.
 5" D.Fir S.24°W., 47.0 ft. mkd. S10 CS BT.
 9" D.Fir N.38°E., 111.2 ft. mkd. T28S R4W S2 CS BT.
 11" D.Fir N.70°W., 87.0 ft. mkd. T28S R4W S3 CS BT.

continued next page

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. cor. for 2, 3, 10 and 11

| | | | |
|-------|-------|-------------|-------|
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |

| |
|---|
| <p>Fd. OK, B. Holt, Oct. 1981, M 90-5</p> |
| <p>David Edwards - For: Seneca Jones Timber Co. - 4/2001 - M 138-8 & C.S. File 65/34-5 6 & B</p> <p>-----</p> <p>Found - BLM brass cap. 17" dia., Fir bears S.41°E., 57.6 ft. 22" dia., Fir bears N.38°E., 111.2 ft. 24" dia., Fir snag bears N.40°W., 5.6 ft.</p> <p>New BTs- 12" dia., Fir bears S.46°W., 26.17 ft. 16" dia., Cedar bears N.41½°W., 35.27 ft.</p> |
| <p>Kris DeGroot - For Seneca Jones Timber Co. - 3/2009 - M157-11</p> <p>-----</p> <p>Found - 2½" iron post with a brass cap by Zirpel and Glenn per 1958 US BLM dependant resurvey (properly) marked, from which a BT by Godfrey in 1964 A 20" fir bears S.41°E., 57.0 ft Bearing trees by Edwards in 2001 per M138-8: A 19" cedar bears N.41°30'W., 35.5 ft with A 16" fir bears S.46°W., 26.3 ft.</p> <p>New BT - A 10" fir bears N.14°45'E., 29.4 ft scribed "T28S R4W S2 BT".</p> |
| |