

PRIMARY CORNER DESCRIPTION Cl. Cor. Secs. 3 & 2 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, Under Contract #44 dated May 30, 1854 (DCSO Records, Volume 12 Pages 5044-45)

-----  
Set a post, cor. of secs. 2 & 3, from which  
A Chinquapin 8" dia. bears S.15°W., 22 lks. dist.  
A R.Fir 36" dia. bears S.62°E., 62 lks. dist.

GLO survey of Exteriors of T28-4 by W.H. Byars, under Contract #376 dated Jan.22, 1881 (DCSO records, Volume 12 Page 5081)

-----  
Set new post as per instructions, from which  
A Maple 5" dia. bears N.25°E., 17 lks. dist.  
A Fir 35" dia. bears N.60°W., 21 lks. dist.  
A Fir 20" dia. bears S.55°E., 31 lks. dist.  
A Maple 3" dia. bears S.41°W., 15 lks. dist.

BLM Dependent Resurvey by Zirpel and Glenn Under Special Instructions dated August 29, 1957 (DCSO Rec, Vol 29 Pg 12222)

-----  
Point for the closing cor. of secs. 2 and 3, on the N. bdy. T 28 S., R. 4 W., at proportionate distance, there is no remaining evidence of the original corner. Set an Iron post, 28" long, 2½" dia. 22" in the ground, with brass cap mkd.

T27S R4W  
S 34  
-----  
S 3 | S 2  
T28S R4W  
C C

1958 from which  
A Fir 40" dia bears S.30½°E. 54¼ lks mkd T28S R4W S2 CC BT  
A Fir 6" dia bears S.50°W., 46¼ lks mkd T28S R4W S3 CC BT

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 1/24/2000 - C.S. File 66/14-7

-----  
Found - 1958 BLM BC/IP protrudes 13" above ground.  
40" now 40" dia., D.Fir snag with a fully healed single blaze, bears S.30½°E., 35.8 ft. (1958)  
6" Fir now 18" dia., Hemlock with a fully healed blaze, bears S.50°W., 30.5 ft. (1958)  
1958 BLM BC/IP S34|S35 bears East, 39.7 ft.  
New BT - 12" dia., Cedar double blazed and scribed "T28S R4W S2 CC CS BT" bears S.26°E., 38.3 ft.

Found OK by D.Edwards, 4/2001 - M138-8 & 65/34-6A & B  
Fd. Ok as per DCSO 2000 ren, by DCSO, J. Pike & S. Flause  
3/10/2008 CS 67/25-30

Cont.

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Cl. Cor. Secs. 3 & 2 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by George M. Winter, Cadastral Surveyors, under Group No. 2704, surveyed July 2013/Feb. 2016 - (DCSO records Vol. 58 page(s) 23349-50)

-----  
The closing cor. of secs. 2 and 3, T. 28 S., R. 4 W., perpetuated by Smith, Deputy Co Surveyor, in 2000, monumented with an iron post, 2½" dia., firmly set, projecting 11" above ground, with brass cap (properly) mkd. from which the remains of bearing trees mkd. by Zirpel and Glenn in 1958

A fir snag, 38" dia., bears S.30½°E., 35.8 ft., with a healed double blaze.

A hemlock, 21" dia., bears S.50°W., 30.5 ft., with no marks visible. (Record, fir) and a bearing tree mkd. by Smith

A cedar, 14" dia., bears S.26°E., 38.3 ft., with scribe marks 8S R4W visible on a partially healed double blaze.

Corner is located in a fenceline extending E. and W.