

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 35; & Sec 2 T 29-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, Contract #44 dated May 30, 1854
(DCSO records Vol. 13 Pg. 5608)

Set 1/4 sec. post at proper dist. from which:
A Laurel, 8" dia. bears S.35°W., 20 lks. dist.
A Laurel, 24" dia. bears N.10°W., 33 lks. dist.

South boundary of T.28-4, surveyed by W.H. Byars, contract # 376, dated Jan. 22 1881. (DCSO records Vol. 13 Pg. 5614)

Set Post for 1/4 sec. cor. from which:
A Laurel, 15" dia. bears N.22°W., 42 lks. dist.
A Cedar, 30" dia. bears S.12°W., 42 lks. dist.
Note: Per note in Byars 1881 survey "In the execution of this work I found that the old line established for the S bdy of this Township was glaringly at fault..." Byars set his own corners See CS 63/166 BLM opinion file T28-4 (added 4/7/2010)

Bruce Shaner-for Longview Fibre Co. 10/81 - 1/82, RM 3-54.

Found - 48" Cedar stump, orig. BT. remains of old face, bears S.12°W., 27.7'.
Root hole of Madrona, orig. BT. (young Madrona about it) bears N.12°W 27.7' (rec. N.22°W.)
U.S.G.L.O. Corner tag faces into corner, signed by H.Langdon, H.Carlson & others Oct. 28, 1945.
U.S.G.L.O. Witness tag faces corner, signed by Burt Holt (circa 1940)
Cruiser blaze "K" faces corner (Al Keatley, Stomar Lumber Co.)(circa 1955)
New BTs- 10" D.Fir, bears S.49°E., 12.0' mkd. ¼ S2 BT.
10" D.Fir, bears N.45°E., 11.2' mkd. ¼ S35 BT.
Set Brass Cap mkd. T28S R4W T29S 1/4 S35 S2 BT RLS 430, 1981.

Ken Hoffine - For: Lone Rock Timber Co. - Feb. 2011 - M157-39

Found - 13" D.Fir bears N.46°E., 10.8 ft (record N.45°E., 11.2 ft) healed face and tag
28" D.Fir bears N.28¼°W., 46.3 ft (unrecorded, unreadable BT Tag and healed face)
39" Cedar stump bears S.9°W., 27.8 ft (rec S.12°W., 27.7 Ft) BT Tag
14" D.Fir S.48½°E., 11.9 ft (record S.49°E., 12.0 ft) healed face and tag
2½" metal pipe (unrecorded) bears Northeast of corner 1.4 ft corner lies on steep South facing slope approximately 330 ft S.20°W., from middle of landing on 29-4-2.1 road.

continued next page

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 35; & Sec. 2 T. 29-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates
Professional Land Surveyors - 2024 - M185-29 A/D

Found - Brass cap by RLS 430 on a 2" I.P. 0.6' above ground
16" Fir bears N.45°E. 11.2' to a nail left side
center with healed blaze and BT tag. (Rec calls
N.45°E. 10.8' BT tag reads S.45°W. 11.2'
matching 1981/82 record)
17" Fir bears S.47¾°E. (S.49°E.) 11.9' with healed
blaze and K-tag.
31" Fir bears N.28½°W. 46.3' to a nail right side
center with healed blaze and illegible tag.
39" rotted cedar stump bears S.9°W. 27.8' with BT tag.
2½" I.P. (Unrecorded) bears N.E. 1.4'
New - Added new BT tags and nails (per above locations)
to Bts.