

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 & 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Page 5623)

-----  
Marked a Cedar 14" dia., for ¼ sec. cor., from which  
Maple 8" dia., bears N.50°E., 14 lks. dist.  
Fir 8" dia., bears S.45°W., 8 lks. dist.

BLM resurvey by James E. Jelley, under Group #570 - Survey, July/July 1965 (DCSO records, Vol. 33 Page 13940)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd:  
T 28 S R 4 W  
¼  $\frac{S\ 14}{S\ 23}$   
1965

from which  
A Cedar 30" dia., bears N.40°W., 72 lks. dist.,  
mkd. ¼ S14 BT.  
A Cedar 8" dia., bears S.0½°E., 43 lks. dist.,  
mkd. ¼ S23 BT.

Dan Saily, Lone Rock Timber Co. - Crew: Brett Ragon, Ignacio Roman & Trevor Clemo - 12/2023 - M183-27

-----  
Found - 1965 BLM brass cap and iron pipe (properly mkd) The monument is 0.2 ft. above ground on west edge of old overgrown logging road. We set 5½ f. galvanized steel post 1 ft. north.  
14" D.Fir bears N.14¼°E., 25.5 FT. (N.12¼°E., 23.8 Ft. (36 lks)) with well healed face  
17" Cedar fd as per record S.0½°E., 28.38 ft. (43 lks) with BLM tag and well healed face.  
New - 11" D.Fir bears N.65¾°E., 13.3 ft. we tag and scribe ¼ S14 BT.  
11" D.Fir bears S.48½°W., 24.2 ft. we tag and scribe ¼ S23 BT.