TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 page 5624)

Set Yew post for ¼ sec. cor., from which:
Fir 6" dia., bears N.30°E., 11 lks.
Fir 11" dia.,bears S.15°E., 16 lks.

BLM resurvey by Bedell and Rogers, under Group #1398. Survey, Sept. 1987/Jan. 1991 (DCSO records, Vol. 49 Page 18682)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd: T 28 S R 4 W

¼ S 11 / S 14
1987

from which
A Yew 8" dia., bears S.10°W., 42 lks. dist. mkd. ¼ S14 BT.
A Cedar 15" dia.,bears N.67°W., 18½ lks. mkd. ¼ S11 BT.
Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

David Edwards - For: Roseburg Resources - 11/2008 - M 158-30

Found - Brass cap
15" dia., cedar bears N.67°W., 12.2 ft. BLM
New BT- 28" dia., cedar bears S.83°W., 36.0 ft.
Set - 6 ft. steel post 2' East.